

Catalog Number: NC08-S/100M
Product ID: 7TCA298000R0184
UPC Number: 78621014685
EAN Number: 05020963023545
Status: Active

Standard Weight, General Purpose Slit Conduit, NC Size 08/NW Size 7.5, Outside Diameter 10.0mm, Inside Diameter 6.5mm, Static Bend Radius 15mm, High Flexibility and Fatigue Life, IP40 Rating, Polyamide 6, Reel Length 100 Meters, Black

North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5540 Flexible Non-Metallic Conduit
Brand Name	Harnessflex
Type	Slit Standard Weight Conduit
Application	General Purpose
Standard	ADR Approved, RoHS, Conforms with End of Life Vehicle Directive (ELV)EU200/53/EC
Trade Size	NC08/NW7.5
Outside Diameter	10.0mm
Inside Diameter	6.5mm
Length	100 m
Radius	Static Bend Radius 15mm
Flexibility	Very High
Material	Polyamide/Nylon 6
Color	Black

European Specifications (ETIM)

ETIM	EC001175 Corrugated plastic hose
Nominal diameter	8mm
Nominal size in inch	1/8 inch
Outer diameter	10mm
Inner diameter	6.5mm
Material	Polyamide 6
Operating temperature	-40-+120°C
Degree of protection (IP)	IP40
Fire resistance in accordance with UL94	HB
UV resistant	Y
Colour	Black
Sheathing material	Not sheathed
Bending strength	Flexible
Lengthwise slotted	Y
Halogen free	Y

Packaging

Outer Quantity	1
Outer Dimensions (inches)	17x17x12
Weight Uom	4.19 lbs. Each

Header

3D Model Available on Website

For further technical assistance, please contact us...

Thomas & Betts - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
 www.tnb.com

T&B Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email:techsupport@tnb.com