

Actual



Representative

 Catalog Number:
 SP-NPT12-B

 Product ID:
 7TAD105330R0000

 UPC Number:
 78621090888

 EAN Number:
 05415022259582

Status: Active

Spiral Cable/Cord Fitting with Intergral Strain-Relief, Trade Size 1/2 Inch, Cable Range 0.197 to 0.394 Inch, IP68 Rating, Polyamide 6 Body and Cap, Neoprene Sealing Ring, Black

 Strain-relief is integral to the fitting, saving time and costs of additional parts for cable/ cord installations.

| North American Specifications (UNSPSC) |  |
|--|--|
| UNSPSC                                 | 39121431 Cable gland connector                 |
| IGCC                                   | 4601 Cable gland connector                     |
| Brand Name                             | T&B  |
| Туре                                   | Cord/Cable Fittings                            |
| Special Features                       | Meets VDE ratings for European Aplications     |
| Application                            | Ideal in Environments Where Maximum Protection |
|  | is Needed Against Conductor Fatigue Caused by  |
|  | Flexing Cables                                 |
| Standard                               | UL E13938                                      |
| Size                                   | 1/2 Inch                                       |
| Conductor Range                        | 0.197 to 0.394 Inch                            |
| Material                               | Polyamide/Nylon 6                              |
| Color                                  | Black  |
| NEMA Rating                            | 4  |
| Temperature Rating                     | -30 to +80 Degrees C                           |

| European Specifications (ETIM)           |                            |  |
|--|----------------------------|--|
| ETIM                                     | EC000441 Cable screw gland |  |
| Thread type                              | NPT                        |  |
| Nominal thread size inch/gas pipe thread | 1/2 inch                   |  |
| Thread length                            | 14.99mm                    |  |
| Suitable for cable diameter              | 5.0038-10.0076mm           |  |
| Material                                 | Plastic                    |  |
| Material quality                         | Polyamide (PA)             |  |
| Degree of protection (IP)                | IP68                       |  |
| Colour                                   | Black                      |  |
| Model                                    | Straight                   |  |
| Operating temperature                    | -30-+80°C                  |  |

| Packaging                 |                   |
|---------------------------|-------------------|
| Outer Quantity            | 50                |
| Outer Dimensions (inches) | 21x5.75x8.75      |
| Weight Uom                | 6.25 lbs. per 100 |

## **Documents / Support Tools**

Technical Drawing / Data Sheet WSD-000010

## Header

3D Model Available on Website

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 860 Ridge Lake Blvd. Memphis, TN 38120

Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

Hours: 7AM - 6PM CDT

Thomas & Betts - USA 860 Ridge Lake Blvd. Memphis, TN 38120 www.tnb.com