



Representative

**Catalog Number:** LT9100P  
**Product ID:** 7TAD012550R0017  
**UPC Number:** 78621045074  
**EAN Number:** 05414363100713  
**Status:** Active

1 Inch 90 Degree Non-Metallic Liquidtight Bullet Connector

- Outside surface has friction reducing ridges.
- Inner surface teeth bite into conduit or tubing to enhance clamping and sealing action.
- Fitting ferrule designed to accept variations in conduit sizes and field conduit cuts.
- Smooth ferrule profile reduces friction to ensure a tight conduit-to-fitting seal.
- Suitable for hazardous locations; Class I Div 2; Class II Div 1 & 2; Groups E, F, G; Class III per N.E.C.; Article 501-4, 502-4 and 503-3

#### North American Specifications (UNSPSC)

|             |                                                                                                                                                                                                 |
|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| UNSPSC      | 39121420 Liquid tight connectors                                                                                                                                                                |
| IGCC        | 4585 Liquid tight connectors                                                                                                                                                                    |
| Brand Name  | T&B                                                                                                                                                                                             |
| Type        | Bullet-90 Degree                                                                                                                                                                                |
| Application | T&B Bullet meets performance requirements when terminating Type B liquidtight non-metallic conduit or flexible non-metallic tubing to a box or enclosure with knockout opening or threaded hub. |
| Standard    | UL E23018, CSA                                                                                                                                                                                  |
| Size        | 1 Inch                                                                                                                                                                                          |
| Material    | Thermoplastic                                                                                                                                                                                   |

#### European Specifications (ETIM)

|                        |                                                       |
|------------------------|-------------------------------------------------------|
| ETIM                   | EC001178 Screw connection for protective plastic hose |
| Nominal size in inch   | 1 inch                                                |
| Model                  | 90°-elbow                                             |
| Revolving thread       | N                                                     |
| Construction type      | External thread                                       |
| Type of connection     | Thread                                                |
| Thread connection size | Other                                                 |
| Thread length          | 18.44mm                                               |
| Material screw gland   | Other                                                 |
| Material sealing       | Other                                                 |
| Colour                 | Black                                                 |

#### Packaging

|                           |                 |
|---------------------------|-----------------|
| Inner Quantity            | 5               |
| Inner Dimensions (inches) | 8x5x4           |
| Outer Quantity            | 25              |
| Outer Dimensions (inches) | 26.75x8.5x5     |
| Weight Uom                | 25 lbs. per 100 |

#### Documents / Support Tools

|                                       |                      |
|---------------------------------------|----------------------|
| Technical Drawing / Data Sheet US     | Available on Website |
| Technical Drawing / Data Sheet Canada | Available on Website |
| Instruction Sheet                     | TA00998-TB2          |

#### Header

|          |                      |
|----------|----------------------|
| 3D Model | Available on Website |
|----------|----------------------|

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
860 Ridge Lake Blvd.  
Memphis, TN 38120  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
MS 3B-50  
860 Ridge Lake Blvd.  
Memphis, TN 38120

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)