




NOTES:

1. MATERIAL: NYLON 6,6
2. FLAMMABILITY: UL94V-2
3. OPERATING TEMPERATURE RANGE: -40°F [-40°C] TO 185°F [85°C]
4. MINIMUM TENSILE RATING: 40 LBS [178 N]
5. MINIMUM WIRE BUNDLE: .0625 [1,59]
6. MAXIMUM WIRE BUNDLE: SEE TABLE
7. INSTALLATION TOOL/SETTING: WT199/1-3 (MS90387-1) OR ERG299/1-3

CATALOG NUMBER	MAXIMUM WIRE BUNDLE	A
L-8-40-**-**	2.000 [50,8]	8.510 [216,15]
L-8-40FL-**-**	2.000 [50,8]	8.510 [216,15]
L-11-40-**-**	3.000 [76,2]	11.287 [286,69]
L-14-40-**-**	4.000 [101,6]	14.287 [362,9]

* = COLOR CODE - 0= BLACK (OUTDOOR) 4= YELLOW 8= GRAY 17= FLUORESCENT YELLOW
 1= BROWN 5= GREEN 9= NATURAL 18= FLUORESCENT GREEN
 2= RED 6= BLUE 11= FLUORESCENT PINK 20= FLUORESCENT BLUE
 3= ORANGE 7= PURPLE 16= FLUORESCENT ORANGE

** = PACKAGING- C= STD PKG (100) D= BULK PKG (500) M= BULK PKG (1,000)

CONSULT CUSTOMER SERVICE FOR PACKAGE QUANTITY AVAILABILITY

FLUORESCENT COLORS NOT "UR" OR "CE" RECOGNIZED OR LISTED

GENERAL NOTES			
1. ALL DIMENSIONS ARE FOR REFERENCE ONLY.			
2. DIMENSIONS IN BRACKETS [] ARE IN METRIC UNITS.			
REVISIONS			
- SEE ERN (****) FOR APPROVAL SIGNATURES & RELEASE DATE. PROJECT NO: ****			
ORIGINAL PROJECT NO / (ERN NO)		SHEET NO:	DRAWING NO:
FM401182 / (2006127)		1 OF 1	WSD-000221
DESCRIPTION: 8", 11" & 14" SERIES 40 INTERMEDIATE CABLE TIES			

Thomas & Betts
 www.tnb.com