




## Display/Operation

|                    |     |
|--------------------|-----|
| Function indicator | yes |
| Power indicator    | no  |

## Electrical connection

|                                   |                            |
|-----------------------------------|----------------------------|
| Connection                        | M12x1-Male, 4-pin, A-coded |
| Polarity reversal protected       | yes                        |
| Protection against device mix-ups | yes                        |
| Short-circuit protection          | yes                        |

## Electrical data

|                                   |                 |
|-----------------------------------|-----------------|
| Load capacitance max. at Ue       | 1 µF            |
| Min. operating current Im         | 0 mA            |
| No-load current Io max., damped   | 12 mA           |
| No-load current Io max., undamped | 8 mA            |
| Operating voltage Ub              | 10...55 VDC     |
| Output resistance Ra              | 100.0 kOhm + 2D |
| Protection class                  | II              |
| Rated insulation voltage Ui       | 250 V AC        |
| Rated operating current Ie        | 200 mA          |
| Rated operating voltage Ue DC     | 24 V            |
| Rated short circuit current       | 100 A           |
| Ready delay tv max.               | 10 ms           |
| Residual current Ir max.          | 10 µA           |
| Ripple max. (% of Ue)             | 15 %            |
| Switching frequency               | 300 Hz          |
| Utilization category              | DC -13          |
| Voltage drop static max.          | 2.5 V           |

## Environmental conditions

|                         |                                 |
|-------------------------|---------------------------------|
| Ambient temperature     | 0...60 °C                       |
| Contamination scale     | 3                               |
| EN 60068-2-27, Shock    | Half-sinus, 30 gn, 11 ms        |
| EN 60068-2-6, Vibration | 55 Hz, amplitude 1 mm, 3x30 min |
| IP rating               | IP67                            |

## Functional safety

|              |       |
|--------------|-------|
| MTTF (40 °C) | 355 a |
|--------------|-------|

## General data

|                     |                   |
|---------------------|-------------------|
| Approval/Conformity | CE<br>EAC<br>WEEE |
| Basic standard      | IEC 60947-5-2     |

## Material

|                          |               |
|--------------------------|---------------|
| Housing material         | Brass         |
| Material sensing surface | LCP           |
| Surface protection       | nickel plated |

## Mechanical data

|                   |              |
|-------------------|--------------|
| Dimension         | Ø 12 x 65 mm |
| Installation      | quasi-flush  |
| Size              | M12x1        |
| Tightening torque | 10 Nm        |

## Output/Interface

|                  |                        |
|------------------|------------------------|
| Switching output | PNP normally open (NO) |
|------------------|------------------------|

Inductive Sensors  
**BES M12MI-PSH80B-S04G**  
Order Code: BES01ZN

**BALLUFF**

Range/Distance

|                               |        |
|-------------------------------|--------|
| Assured operating distance Sa | 5.8 mm |
| Hysteresis H max. (% of Sr)   | 15.0 % |
| Rated operating distance Sn   | 8 mm   |

|                                  |        |
|----------------------------------|--------|
| Real switching distance sr       | 8 mm   |
| Repeat accuracy max. (% of Sr)   | 10.0 % |
| Switching distance marking       | ■■■■   |
| Temperature drift max. (% of Sr) | 20 %   |
| Tolerance Sr                     | ±10 %  |

Remarks

Quasi-flushed: See installation instructions for inductive sensors with extended range 825356.  
The sensor is functional again after the overload has been eliminated.  
For further information about the MTTF and B10d see MTTF / B10d certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

Connector Drawings



Wiring Diagrams

