
Detailed Specifications & Technical Data

ENGLISH MEASUREMENT VERSION



AX100282 Faceplates and Panels - Patch Box - MDVO



Suitability - Indoor:

Notes (Overall)

Transmission Characteristics (Connectivity)





For more Information please call

1-800-Belden1



General Description: MDVO Patch Box, 12-port, Black (Empty) Usage (Overall) Suitable Applications: Compatible with a variety of modules that are suitable for use with Belden IBDN Systems 10GX, 4800, 3600, 2400 and 1200 Related Parts: - Compatible with 10GX, CAT6+ and CAT5E MDVO Modular Jacks **Physical Characteristics (Connectivity)** Capacity Max. Capacity: 12 connectors Access Front Connection: Flush Termination Area: Front **Dimensions** Dimensions: 2.747 10.000 **Materials** Materials: Description Material Patch Box Steel Plastic - UL94V-0 Bezel Color Color: Black Weight Weight: 2.525 lbs. **Included Parts** Included Parts: 2 Screws Wood #10x1in; Label **Packaging** Packaging: Individually packaged in a cardboard box. **Mechanical Characteristics (Connectivity)** MDVO-Style Footprint/Type: Storage Temperature Range: -40°C To +70°C Installation Temperature Range: -10°C To +60°C -10°C To +60°C **Operating Temperature Range: Applicable Specifications and Agency Compliance (Overall) Applicable Standards & Environmental Programs** EU Directive 2002/95/EC (RoHS): EU RoHS Compliance Date (mm/dd/yyyy): 07/01/2006 MII Order #39 (China RoHS): Safety Listing: ACA, Bi-national Standard Listed Suitability

Yes

Page 1 of 2 11-10-2016

Detailed Specifications & Technical Data

ENGLISH MEASUREMENT VERSION



AX100282 Faceplates and Panels - Patch Box - MDVO

Notes: For proper installation refer to Installation Guide PX100394 included with the product or visit our web site at http://www.belden.com

Product Family

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
AX100282	1 EA	2.550 LB	BLACK		MDVO PATCH BOX 12-PORT

Revision Date: 02-24-2012 Revision Number: 0

© 2016 Belden, Inc All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/5FC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Page 2 of 2 11-10-2016