

735AS3P Coax - Bundled 735 Plenum Telecommunication Coax



For more Information
please call

1-800-Belden1

**General Description:**

3-26 AWG solid silver plated copper conductors, foam FEP insulation, Beldfoil® shield (100% coverage) plus a tinned copper braid shield (95% coverage), Flammarrest® jacket. Banana Peel®.

Physical Characteristics (Overall)**Conductor**

AWG:

# Coax	AWG	Stranding	Conductor Material	Dia. (in.)
3	26	Solid	SPC - Silver Plated Copper	0.016

Total Number of Conductors: 3

Insulation

Insulation Material:

Insulation Trade Name	Insulation Material	Dia. (in.)
Teflon	FFEP - Foam Fluorinated Ethylene Propylene	0.077

Fillers

Fillers: Extruded PVC Spline

Inner Shield

Inner Shield Material:

Layer #	Inner Shield Trade Name	Type	Inner Shield Material	Coverage (%)
1	Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100.000
2		Braid	TC - Tinned Copper	93.000

Inner Jacket

Inner Jacket Material:

Inner Jacket Trade Name	Inner Jacket Material	Nom. Dia. (in.)
Flammarrest(R)	LS PVC - Low Smoke Polyvinyl Chloride	0.129

Overall Cable

Overall Nominal Diameter: 0.393 in.

Mechanical Characteristics (Overall)

Operating Temperature Range:	-20°C To +75°C
UL Temperature Rating:	60°C
Non-UL Temperature Rating:	75°C
Bulk Cable Weight:	43 lbs/1000 ft.
Min. Bend Radius (Overall):	2.800 in.

Applicable Specifications and Agency Compliance (Overall)**Applicable Standards & Environmental Programs**

NEC/(UL) Specification:	CMP
CEC/C(UL) Specification:	CMP
EU Directive 2011/65/EU (ROHS II):	Yes
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	11/06/2008
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MIL Order #39 (China RoHS):	Yes

735AS3P Coax - Bundled 735 Plenum Telecommunication Coax

Flame Test

UL Flame Test:	NFPA 262 Plenum Flame Test (UL910)(FT6)
C(UL) Flame Test:	FT6

Suitability

Suitability - Indoor:	Yes
-----------------------	-----

Plenum/Non-Plenum

Plenum (Y/N):	Yes
Non-Plenum Number:	735A3

Electrical Characteristics (Overall)

Nom. Characteristic Impedance:

Impedance (Ohm)
75.000

Nom. Inductance:

Inductance (µH/ft)
0.097

Nom. Capacitance Conductor to Shield:

Capacitance (pF/ft)
17.500

Nominal Velocity of Propagation:

VP (%)
76.000

Nominal Delay:

Delay (ns/ft)
1.340

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
41.000

Nom. Inner Shield DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
5.300

Max. Attenuation:

Freq. (MHz)	Attenuation (dB/100 ft.)
1.000	0.600
1.024	0.610
4.224	1.100
5.000	1.200
10.000	1.700
17.184	2.200
22.368	2.500
25.920	2.700
44.736	3.600
50.000	3.800
69.632	4.500
77.760	4.800
100.000	5.500
137.088	6.400
200.000	7.800

Max. Operating Voltage - UL:

Voltage
300 V RMS

Minimum Return Loss:

Start Freq. (MHz)	Stop Freq. (MHz)	Min. RL (dB)
15.000	95.000	30.000

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
735AS3P 0081000	1,000 FT	47.000 LB	GRAY		BONDED FILLER COMPOSITE
735AS3P 008500	500 FT	25.500 LB	GRAY		BONDED FILLER COMPOSITE

735AS3P Coax - Bundled 735 Plenum Telecommunication Coax

Revision Number: 1 Revision Date: 08-04-2015

© 2016 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).