


AX101852 Modular Connectors - Termination Station



For more Information
please call

1-800-Belden1

General Description:

Termination Station

Usage (Overall)

Suitable Applications:	Terminate 10GX, CAT6+, Cat5E MDVO and Keyconnect Style Module, Mediaflex Gigaflex Inserts
Related Parts:	10GX, CAT6+, Cat5E MDVO and Keyconnect Style Module, Mediaflex Gigaflex Inserts

Physical Characteristics (Connectivity)

Dimensions

Dimensions:

Height (in.)	Width (in.)	Depth (in.)
2.500	5.600	7.000

Materials

Materials:

Description	Material
Termination Station	Plastic - UL940V-0

Color

Color: Black

Weight

Weight: 0.100 lbs.

Packaging

Packaging: Individually packaged in a clear plastic bag, Standard shipping carton of 10 units

Mechanical Characteristics (Connectivity)

Storage Temperature Range:	-40°C To +70°C
Installation Temperature Range:	-10°C To +60°C

Applicable Specifications and Agency Compliance (Overall)

Suitability

Suitability - Indoor: Yes - Indoor

Transmission Characteristics (Connectivity)

Notes (Overall)

Notes: For proper installation refer to Installation Guide PX103206 available on our web site at <http://www.belden.com>

Product Family

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
AX101852	1 EA	0.333 LB	BLACK		MEDIAFLEX TERMINATION STATION

Revision Number: 0 Revision Date: 06-05-2009

© 2016 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale.