



## PRODUCT DATA SHEET

Constant Velocity (CV) Joint Grease, 4 Wt Oz (Discontinued)  
Part Number: SL3174B

**Product  
Discontinued**

Product Description	A special lithium base grease fortified with molybdenum disulfide and polymers. It is used for the installation & repair work on CV joints. Will extend the life of the CV joint & the additives will sustain the shock loads encountered in the CV joints
Applications	CV boot, CV joints found in front wheel drive passenger vehicles, safe for both domestic & foreign CV joints
Unit Package Description	4 ounce Tube
Brand	Sta-Lube
Generic Description 1	Constant Velocity Joint Grease
Net Fill	4 Wt Oz
UPC Code	072213317428
Unit Dimensions	7.5H x 2.5W x 1.5D in
Units Per Case	36
Case Dimensions	8.38H x 9.5W x 9.2D in
Cases Per Pallet	100
Case Weight	11 lbs
I 2 of 5 Code	30072213317429
Appearance	Dark Gray Semi-Solid to Solid Grease
Base Type	Lithium-12
Flash point (F)	>450°F
Flash point (C)	>232°C
Flammability Class - CPSC	None
Spec Gravity Concentrate	0.9 at 60°F
NLGI Grade	1
Timken OK Load [Lbs.]	50 Lbs
Plastic Safe	Not Determined
Evaporation Rate	<0.01 (Butyl Acetate=1)
Working Temp (F)	10 to 275°F

Last revised: 8/6/2015  
Page 1 of 2



Customer Care: 800-556-5074  
Technical Assistance: 800-521-3168  
[www.crcindustries.com](http://www.crcindustries.com)

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.



## PRODUCT DATA SHEET

Product  
Discontinued

Working Temp (C)	-12.2 to 134°C
4 Ball EP	Not Determined
4 Ball Wear	Not Determined
Drop Point	350°F
Elastomer Compatibility	0 to 40% vol ; 0 to 15 hard
Leakage	Not Determined
Oil Separation	<10%
Oxidation Stability	<5 Lbs
Pour Point (F)	10°F
Pour Point (C)	-12.22°C
ISO Viscosity Grade	110
Water Washout	Not Determined
Worked Penetration	300 to 330
Propellant	None
DOT Proper Shipping Name	Not Regulated
VOC % (Federal)	<0.1
VOC g/L (Federal)	<0.9
VOC Lbs./Gal. (Federal)	<0.007
VOC Category	Not Regulated
Removal (How To)	Remove with a degreaser or brake cleaner product.

Last revised: 8/6/2015  
Page 2 of 2



Customer Care: 800-556-5074  
Technical Assistance: 800-521-3168  
[www.crcindustries.com](http://www.crcindustries.com)

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.