

PRODUCT DATA SHEET

Silaramic® Brake System Grease, 5 Wt Oz Part Number: 05361

Product Description

Applications

Brand

Net Fill

UPC Code

Base Type

NLGI Grade

Plastic Safe

A synthetic, dry-film, ceramic lubricant formulated to reduce brake noise and vibrations by dampening all brake vibrating frequencies. Will not run off or wash out. Works in extreme temp ranges from -50 to 3000°F. Protects against uneven pad wear.

All brake systems and brake components, including calipers, bushings, holes, pins, inserts, anchors, bolts, calipers and boots

Unit Package Description 5 Ounce Tube CRC Generic Description 1 Brake System Grease 5 Wt Oz 078254053615 6.25H x 2W x 2D in Unit Dimensions Units Per Case 12 8H x 6.38W x 7.63D in **Case Dimensions** Cases Per Pallet 175 5 lbs Case Weight I 2 of 5 Code 30078254053616 Appearance Off White Semi Solid Grease Polydimethylsiloxane Flash point (F) 550°F 288°C Flash point (C) Flammability Class - CPSC None Spec Gravity Concentrate 1.0 2 Timken OK Load [Lbs.] Not Determined Yes **Evaporation Rate** Very Slow **Dielectric Strength** Not Determined

> Last revised: 5/4/2016 Page 1 of 2



HIGH TEMP • PURE SILICONE

EMPERATURE

CERAMIC BRAKES

AT HIGHER TEMP

NO. 05361

NET WT. 5 02. (142 0)

Customer Care: 800-556-5074 Technical Assistance: 800-521-3168 www.crcindustries.com



and adheres to the strictest guidelines for quality in all facets of research, development and production. $CRC^{\circledast}, K\&W^{\circledast}, Sta-Lube^{\circledast}, Marykate^{\circledast} and products denoted with <math display="inline">^{\circledast}$ and $^{\intercal}$ are trademarks

of CRC Industries, Inc.

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair



PRODUCT DATA SHEET



Working Temp (F) Working Temp (C) 4 Ball EP 4 Ball Wear **Drop Point** Elastomer Compatibility Leakage Low Temp Torque **Oil Separation Oxidation Stability** Pour Point (F) Water Washout Worked Penetration Propellant DOT Proper Shipping Name VOC % (Federal) VOC g/L (Federal) VOC Lbs./Gal. (Federal) **VOC Category** Removal (How To)

-50 to 3000°F -45.6 to 1648.89°C Not Determined Not Determined None Compatible 0.2 Not Determined 0.2 Not Determined Not Determined 0.25 265 to 295 None Not Regulated 0 0 0 Not Regulated

Remove with petroleum solvents.



Customer Care: 800-556-5074 Technical Assistance: 800-521-3168 www.crcindustries.com



 $CRC^{\circledast}, K\&W^{\circledast}, Sta-Lube^{\circledast}, Marykate^{\circledast} and products denoted with <math display="inline">^{\circledast}$ and $^{\intercal}$ are trademarks of CRC Industries, Inc.

and adheres to the strictest guidelines for quality in all facets of research, development and production.

Last revised: 5/4/2016 Page 2 of 2