

## **PRODUCT DATA SHEET**

Quick Dry Moly Lube, 14 Wt Oz Part Number: 03043

**Product Description** 

Applications

Brand

Net Fill

UPC Code

Appearance

Plastic Safe

Film Type

Base Type

Industrial

cante con Molibden

a Duraci

Net Wt. 14 0Z.

Peso Neto: 397 g (140

VAPOR H

ABLE, EL VAPOR ES

CONTENIDO BAJO PR

de Secado Rápido

Lowers friction, prevents galling and helps to reduce torque and energy consumption. High anti-friction and anti-seizure properties. Fast drying film resists dirt and dust build-up.

Gaskets, transfer belts, conveyor belts, motors, plant machinery and handling equipment, rubber moldings, high temperature, low load, or high rpm slides, rollers, wheels, gears, chains & hoists

Unit Package Description 16 Ounce Aerosol CRC **Generic Description 1** Dry Film Lubricant 14 Wt Oz 078254030432 7.75H x 2.63W x 2.63D in Unit Dimensions Units Per Case 12 **Case Dimensions** 8.1H x 8.3W x 11.1D in Cases Per Pallet 152 11 lbs Case Weight | 2 of 5 Code 30078254030433 Black Liquid **Organic Solvents** Flash point (F) 54°F 12°C Flash point (C) Flammability Class - CPSC Flammable Spec Gravity Concentrate 1.32 No Dry **Evaporation Rate** Fast Working Temp (F) 650°F Working Temp (C)

> Last revised: 3/2/2016 Page 1 of 2



Customer Care: 800-556-5074 Technical Assistance: 800-521-3168 www.crcindustries.com



and adheres to the strictest guidelines for quality in all facets of research, development and production.

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair

343.3°C

 $CRC^{\circledast}, K\&W^{\circledast}, Sta-Lube^{\circledast}, Marykate^{\circledast} and products denoted with <math display="inline">^{\circledast}$  and  $^{\intercal}$  are trademarks of CRC Industries, Inc.



## **PRODUCT DATA SHEET**

Propellant Aerosol Flammability Level DOT Proper Shipping Name VOC % (Federal) VOC g/L (Federal) VOC Lbs./Gal. (Federal) **VOC Category** Removal (How To)

Hydrocarbon Ш Aerosols, Flammable, Limited Quantity 27 356.4 2.97 Dry Lubricant Remove with petroleum solvents.

<sup>ubricante</sup> con Molibde de Secado Rápido

Industrial

a Duri

Net Wt. 14 oz. Peso Neto: 397 g (140

LAMMABLE, VAPOR H YE AND SKIN I R PRESSURE. Read warming

AMABLE, EL VAPOR ES P S PERJUDICIAL O MORT CONTENIDO BAJO PRES



Customer Care: 800-556-5074 Technical Assistance: 800-521-3168 www.crcindustries.com



and adheres to the strictest guidelines for quality in all facets of research, development and production.  $CRC^{\circledast}, K\&W^{\circledast}, Sta-Lube^{\circledast}, Marykate^{\circledast} and products denoted with <math display="inline">^{\circledast}$  and  $^{m}$  are trademarks

of CRC Industries, Inc.

Last revised: 3/2/2016 Page 2 of 2