

PRODUCT DATA SHEET

Bright Zinc-It® Instant Cold Galvanize, 13 Wt Oz No. 18414 | Item# 1005244 | Case# 1005243

Product Description An acrylic based, sacrificial zinc coating that protects

ferrous metals from oxidizing. Creates a barrier film between the environment & the base metal to prevent the

formation or spread of rust & corrosion.

Color

Applications On threads, exposed edges, fasteners, conduit, strapping,

> welds, fencing, railings, grates, electrical poles, breaker panel housings, rain spouts, signs, doors, trailers, waste

containers, catwalks, and guard rails.

Unit Package Description 16 Ounce Aerosol

CRC **Brand**

Generic Description 1 Cold Galvanized Coating

Net Fill 13 Wt Oz

UPC Code 078254184142

Unit Dimensions 7.75H x 2.63W x 2.63D in

Units Per Case 12

Case Dimensions 8.68H x 5.62W x 11.31D in

Cases Per Pallet 150 Case Weight 13 lbs

I 2 of 5 Code 30078254184143

Appearance Gray Liquid

Flash point (F) -2.2°F

Flash point (C) -19°: C

Flammability Class - CPSC Extremely Flammable

Spec Gravity Concentrate 0.77 to 0.85

Plastic Safe No

Evaporation Rate Fast

Dry Time - Fully Dry 48 Hours Dry Time - Tack Free 20 Minutes

Recoat 20 Minutes to 16 Hours

Last revised: 11/30/2017

Page 1 of 2



Bright Zinc-It

Instant Cold Galvanize

Est Shine Correction Inhibitor

thirs over 65% Zinc

forms to ASTM A780

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified

of CRC Industries, Inc.



PRODUCT DATA SHEET

Coverage 28 to 32 Sq Ft per aerosol

Working Temp (F)

Working Temp (C)

Not Determined

Propellant

Hydrocarbon

Aerosol Flammability Level III

Military Specification Not Determined

Number

CRC

Instant Cold

Contains over 65% Zinc Contains to ASTM A780

Est Shine Correction Inhibitor

Galvanize

Bright Zinc-It®

DOT Proper Shipping Name Aerosols, Flammable, Limited Quantity

VOC % (Federal) 45.9 VOC g/L (Federal) 579 VOC Lbs./Gal. (Federal) 4.83

VOC Category Aerosol Coating: Metallic

MIR Limit (EPA) 1.9
MIR Limit (CA) 1.25
MIR Value 1.1

Removal (How To) Remove with petroleum solvents.

Last revised: 11/30/2017 Page 2 of 2



