



# PRODUCT DATA SHEET

Bolt Lock Shock Resistant Threadlocker, 1.69 Fl Oz  
(Discontinued)  
No. 04510

Product  
Discontinued

## Product Description

A single component anaerobic threadlocking adhesive, which is thixotropic & develops medium to high strength. The product prevents loosening & leakage of threaded fasteners caused by shock & vibration.

## Applications

Permanent applications where heavy shock and vibration, or extreme environmental conditions are present: refrigeration hardware, differential bolts, construction equipment bolts, bulldozer track bolts, railroad pedestal bolts.

## Unit Package Description

4 Ounce Bottle

## Brand

CRC

## Generic Description 1

Anaerobic Threadlocker

## Net Fill

1.69 Fl Oz

## UPC Code

078254045108

## Unit Dimensions

6.25H x 2.5W x .75D in

## Units Per Case

10

## Case Dimensions

6.75H x 7W x 5D in

## Cases Per Pallet

288

## Case Weight

2 lbs

## I 2 of 5 Code

30078254045109

## Appearance

Red Liquid

## Flash point (F)

>200°F

## Flash point (C)

>93°C

## Flammability Class - CPSC

Combustible

## Spec Gravity Concentrate

1.1

## Plastic Safe

Yes

## Curing Time

24 Hours

## Working Temp (F)

-75 to 300°F

## Working Temp (C)

-59.4 to 148.9°C

Last revised: 7/18/2016  
Page 1 of 2



Customer Care: 800-556-5074  
Technical Assistance: 800-521-3168  
www.crcindustries.com

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.



## PRODUCT DATA SHEET

**Product  
Discontinued**

Viscosity @68 F cP	2500
Gap Fill	0.010 Inches
Shear StrengthSteel Nuts & Bolts	3000 psi
Locking Strength	Medium
Propellant	None
DOT Proper Shipping Name	Not Regulated
Military Specification Number	Meets requirements of Mil-S-46163A Type II Grade O
VOC % (Federal)	31.5
VOC g/L (Federal)	321
VOC Lbs./Gal. (Federal)	2.72
VOC Category	Not Regulated
Removal (How To)	High Heat to Remove

Last revised: 7/18/2016  
Page 2 of 2



Customer Care: 800-556-5074  
Technical Assistance: 800-521-3168  
[www.crcindustries.com](http://www.crcindustries.com)

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.