

PRODUCT DATA SHEET

Cutting Oil Thread Cutting Lubricant, 5 Gal (Discontinued) No. 14052

Product Description Cutting Oil is a superior thread cutting lubricant for use on all types of metals, including brass, copper and aluminum.

Applications Tapping, threading, drilling, sawing, shearing, turning,

and reaming metal parts, pipes, conduit, screws, bolt holes, housings, aluminum sheets, strapping, gears and

chains.

Product Discontinued

Unit Package Description 5 Gallon Pail

Brand CRC

Generic Description 1 Thread Cutting Lubricant

Net Fill 5 Gal

UPC Code 078254140520

Unit Dimensions 13.75H x 11.25W x 11.25D in

Units Per Case 1

Case Dimensions 13.8H x 11.3W x 11.3D in

Cases Per Pallet 24
Case Weight 42 lbs

Appearance Brown Liquid
Base Type Petroleum
Flash point (F) 347°F
Flash point (C) 175°C

Flammability Class - CPSC None
Spec Gravity Concentrate 0.919

Plastic Safe Safe on Acrylic Plastics

Film Type Non-Drying

Evaporation Rate <1 (butyl acetate=1)

Working Temp (F) Max 300°F Working Temp (C) Max 148.9°C

Propellant None NSF Category Code P1

Last revised: 7/12/2016

Page 1 of 2





PRODUCT DATA SHEET

NSF Number 017207

DOT Proper Shipping Name Not Regulated

VOC % (Federal) 0
VOC g/L (Federal) 0
VOC Lbs./Gal. (Federal) 0

VOC Category Cutting or Tapping Oil (Non-Aerosol)

Restricted from Sale In: SCAQMD

Removal (How To) Remove with general purpose degreaser.

Product Discontinued

Last revised: 7/12/2016

Page 2 of 2

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.

