

PRODUCT DATA SHEET

Cutting Oil Thread Cutting Lubricant, 12 Wt Oz No. 14050 | Item# 1004784 | Case# 1004783

Product Description

Cutting Oil is a superior thread cutting lubricant for use on all types of metals, including brass, copper and aluminum.

Applications

Tapping, threading, drilling, sawing, shearing, turning, and reaming metal parts, pipes, conduit, screws, bolt holes, housings, aluminum sheets, strapping, gears and

chains.

Unit Package Description

Generic Description 1

CRC

Brand

Thread Cutting Lubricant

16 Ounce Aerosol

Net Fill

12 Wt Oz

UPC Code

078254140506

Unit Dimensions

7.75H x 2.63W x 2.63D in

Units Per Case

12

Case Dimensions

8.1H x 8.3W x 11.1D in

Cases Per Pallet

133 12 lbs

Case Weight

30078254140507

I 2 of 5 Code **Appearance**

Brown Liquid

Petroleum

Base Type

>300°F

Flash point (F)

Flash point (C)

>149°C

Flammability Class - CPSC

Flammable

Spec Gravity Concentrate

0.924

Plastic Safe

Safe on Acrylic Plastics

Film Type

Non-Drying

Evaporation Rate

Slow

Working Temp (F) Working Temp (C) Max 300°F Max 148.9°C

Propellant

Hydrocarbon

Last revised: 11/28/2017

Page 1 of 2




Lubricante de aceite de

^{Para utilizar en Metales Ferrosos y} no Ferrosos Se Adhiere a Superficies Verticales

Clings to Vertical Surfaces

corte de tornillos roscados Use on Ferrous & Non-Ferrous Metals



and adheres to the strictest guidelines for quality in all facets of research, development and production. CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified



PRODUCT DATA SHEET



P1

NSF Number

017206

Aerosol Flammability Level

111

DOT Proper Shipping Name

Aerosols, Flammable, Limited Quantity

VOC % (Federal)

20

VOC g/L (Federal)

184.8

VOC Lbs./Gal. (Federal)

1.54

VOC Category

Cutting or Tapping Oil (Aerosol)

Restricted from Sale In:

SCAQMD

Removal (How To)

Remove with general purpose degreaser.

Cutting Oil
Thread Cutting
Lubricant
Lubricant
Lubricante de aceite de
Corie de tornillos roscados
Lise on Ferrous & Non-Ferrous Metals
Clinos to Vertical Surfaces
Para utilizar en Metales Ferrosos y
To Ferrosos
Sa Adhiere a Superficies Verticales

DANGER: FLAMMABLE
DES UNDER PRESSURE
DES UNDER PR

Last revised: 11/28/2017

Page 2 of 2



Customer Care: 800-556-5074 Technical Assistance: 800-521-3168 www.crcindustries.com

