



Food Grade Hydraulic Oil ISO 68, 5 Gal No. 04226 | Item# 1003543

Product Description Food grade hydraulic fluid that is formulated with USP

grade white oils. This NSF H1 registered food grade hydraulic fluid is engineered to meet the demanding requirements of severe hydraulic systems using high

pressure and high output pumps.

Applications Great for use in all types of food processing facilities.

Hydraulic Systems, vacuum pumps, canning, bearings,

valves, circulating oil.

Unit Package Description 5 Gallon Pail

Brand CRC

Generic Description 1 Hydraulic Oil

Net Fill 5 Gal

UPC Code 078254042268

Unit Dimensions 15H x 12W x 12D in

Units Per Case 1

Case Dimensions 15H x 12W x 12D in

Cases Per Pallet 36
Case Weight 38 lbs

Appearance Clear Liquid

Flash point (F) 500°F Flash point (C) 260°C

Flammability Class - CPSC Combustible

Spec Gravity Concentrate 0.87

Plastic Safe Safe on Most Plastics (Test small area)

Evaporation Rate Slow I SO Viscosity Grade 68 SAE Grade 20

Working Temp (F) 0 to 375°F

Working Temp (C) -17.8 to 190.6°C

NSF Category Code H1

Last revised: 7/30/2019

Page 1 of 2







NSF Number 144414

DOT Proper Shipping Name Not Regulated VOC % (Consumer Product 0 def)

VOC g/L (Consumer 0 Product def)

VOC lbs/gal (Consumer 0 Prod def)

VOC Category Not Regulated

Removal (How To) Remove with Petroleum Distillates.

Last revised: 7/30/2019

Page 2 of 2

