



Sta-Plex™ Extreme Pressure Premium Red Grease, 14 Wt Oz No. SL3191 | Item# 1007892 | Case# 1007891

Product Description

A superior multi-purpose certified lithium complex based NLGI #2 grease. Contains extreme pressure, anti-wear, & anti-oxidation additives. Ideal for high temperature & performance applications. Drop point 500°F

Applications

Ind. mining, metal production, machining, plastic molding, pumps, electric motors, ball & roller bearings, kilns, assembly plants, drying ovens, trucks, automobiles, buses, construction equipment, off-road operations, tractors mowers, reapers, water pumps

Unit Package Description

14 Ounce Can

Brand

Sta-Lube

Generic Description 1

Premium Red Grease

Net Fill

14 Wt Oz

UPC Code

072213319101

Unit Dimensions

3.44H x 4.13W x 4.13D in

Units Per Case

12

Case Dimensions

3.5H x 12.5W x 17D in

Cases Per Pallet

108

Case Weight

13 lbs

I 2 of 5 Code

30072213319102

Appearance

Red Semi-Solid to Solid Grease

Base Type

Lithium Complex

Flash point (F)

475°F

Flash point (C)

246°C

Flammability Class - CPSC

None

Spec Gravity Concentrate

0.9 at 60°F

NLGI Grade

2

Timken OK Load Lbs.

60 Lbs Min

Plastic Safe

Not Determined

Evaporation Rate

<1 (butyl acetate=1)

Last revised: 6/12/2019

Page 1 of 2



Chemical Solutions to Keep You Moving™
f t y o i n • 800-272-8963 • crcindustries.com

CRC Industries, Inc. is a global leader in the production of specialty chemicals for maintenance, repair and operational professionals and do-it-yourselfers serving the automotive, industrial, electrical, marine, heavy truck, hardware and aviation markets. CRC trademarked brands include: CRC®, K&W®, Sta-Lube®, SmartWasher®, Marykate®, Weld-Aid®, Ambersil®, KF®, Kontakt Chemie®, Ados®, Action Can®, and Kitten®.

©2019 CRC Industries, Inc.



| | |
|---------------------------------|---|
| Working Temp (F) | -20 to 325°F |
| Working Temp (C) | -27 to 162°C |
| 4 Ball EP | 77 LWI, 500 Kg Weld |
| 4 Ball Wear | 0.4 typical; 0.6 Max |
| Drop Point | 500+ °F |
| Elastomer Compatibility | 0 to 30% vol; 0 to 15 hard |
| Leakage | 10g Max |
| Low Temp Torque | 15.5 Max |
| Oil Separation | <5 |
| Oxidation Stability | 5 |
| Pour Point (F) | 5°F |
| Pour Point (C) | -15°C |
| ISO Viscosity Grade | 230 |
| Water Washout | <5 |
| Worked Penetration | 265 to 295 |
| Propellant | None |
| NSF Category Code | H2 |
| NSF Number | 145511 |
| DOT Proper Shipping Name | Not Regulated |
| VOC % (Consumer Product def) | 1 |
| VOC g/L (Consumer Product def) | 9 |
| VOC lbs/gal (Consumer Prod def) | 0.075 |
| VOC Category | Not Regulated |
| Removal (How To) | Remove with a degreaser or brake cleaner product. |

Last revised: 6/12/2019
Page 2 of 2



Chemical Solutions to Keep You Moving™
f t y o i n • 800-272-8963 • crcindustries.com

CRC Industries, Inc. is a global leader in the production of specialty chemicals for maintenance, repair and operational professionals and do-it-yourselfers serving the automotive, industrial, electrical, marine, heavy truck, hardware and aviation markets. CRC trademarked brands include: CRC®, K&W®, Sta-Lube®, SmartWasher®, Marykate®, Weld-Aid®, Ambersil®, KF®, Kontakt Chemie®, Ados®, Action Can®, and Kitten®.

©2019 CRC Industries, Inc.