

Diablo SRL

GUARDIAN
FALL PROTECTION

Part #	Description	Weight
11016	Diablo 6' Single Leg SRL w/Steel Snap Hook	2½ lbs.
11017	Diablo 6' Single Leg SRL w/Aluminum Snap Hook	2¼ lbs.
11018	Diablo 6' Single Leg SRL w/Aluminum Rebar Hook	3 lbs.
11019	Diablo 6' Single Leg SRL w/Steel Rebar Hook	3½ lbs.
11051	Diablo 6' Double Leg SRL Kit w/Steel Snap Hook	5¾ lbs.
11052	Diablo 6' Double Leg SRL Kit w/Aluminum Snap Hook	5½ lbs.
11053	Diablo 6' Double Leg SRL Kit w/Aluminum Rebar Hook	6¾ lbs.
11054	Diablo 6' Double Leg SRL Kit w/Steel Rebar Hook	7¾ lbs.

Compliant with all OSHA 1910, OSHA 1926 Subpart M, ANSI Z359.14-14, and ANSI A10.32-2012 regulations.

Custom configurations available. Not repairable.
Contact customer service for details.

Diablo SRL is suitable for the following applications:



Personal Fall Arrest: Diablo SRL may be used in Personal Fall Arrest applications to support a MAXIMUM 1 Personal Fall Arrest System (PFAS). Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. Maximum permitted free fall is 2' (SRL may be positioned no more than 2' below harness dorsal D-ring or 2' above anchor point).



Restraint: Diablo SRL may be used in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully deployed length of lanyard/SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, Shoulder.

For all applications: worker weight capacity range (including all clothing, tools, and equipment) is 130-420 lbs.

Materials: stainless steel, aluminum, glass-filled nylon, and polyester.

Class A SRL

Average arrest force: 1,350 lbs.

Maximum arrest force: 1,800 lbs.

Maximum deceleration distance: 24".

Carabiner included.

MAXIMUM 1 user per Diablo SRL.

ALWAYS maintain 100% tie-off.

For dual leg kit, assemble and use according to instructions provided with Dual SRL Bracket.

If using Diablo with rebar hook configuration, Diablo must always be worn at harness dorsal D-ring. Rebar hook must ONLY be connected to compatible structural rebar.

