

Thin wall conduit fittings (for EMT conduit)

Straps, clamps, clampbacks/spacers

CLAMPBACKS/SPACERS – MALLEABLE IRON

Applications:

- Provides space between conduit and mounting surface

Standard materials:

- Stamped steel – 1/2" to 1 1/2"
- Malleable iron – 2" to 6"

Standard finish:

- Zinc plated

UL File No. E-184283



Cat. #	Size	Unit qty.	Wt. lbs. per 100
CB1 [Ⓚ]	1/2"	25	8
CB2 [Ⓚ]	3/4"	25	10
CB3 [Ⓚ]	1"	25	12
CB4 [Ⓚ]	1 1/4"	25	21
CB5 [Ⓚ]	1 1/2"	25	42
CB6	2"	10	40
CB7	2 1/2"	10	49
CB8	3"	10	62
CB9	3 1/2"	10	91
CB10	4"	10	110
CB11 [Ⓚ]	5"	5	135
CB12 [Ⓚ]	6"	5	225

[Ⓚ] Stamped steel.

[Ⓚ] Not UL Listed.

STRAPS – STEEL GALVANIZED

Two hole

UL File No. E-184283



Cat. #	Size	Unit qty.	Wt. lbs. per 100
497 1	1/2"	250	2
497 2	3/4"	150	3
497 3	1"	100	5
497 4	1 1/4"	50	8
497 5	1 1/2"	50	13
497 6	2"	25	14
496 9	2 1/2"	25	19
496 10	3"	25	23
496 11	3 1/2"	25	93
496 12	4"	10	108

CLAMPS – MALLEABLE IRON

UL File No. E-184283



Cat. #	Size	Unit qty.	Wt. lbs. per 100
516 [Ⓚ]	2 1/2"	5	104
517 [Ⓚ]	3"	2	120
518 [Ⓚ]	3 1/2"	2	150
519 [Ⓚ]	4"	2	220

[Ⓚ] Also for use with rigid/IMC conduit.

CLAMPS – STEEL

Applications:

- To support EMT conduit to mounting surface

Heavy gauge

UL File No. E-184283



Cat. #	Size	Unit qty.	Wt. lbs. per 100
200	1/2"	100	5
201	3/4"	100	6
202	1"	100	6
203	1 1/4"	50	13
204	1 1/2"	25	17
205	2"	25	20
206 [Ⓚ]	2 1/2"	25	64
207 [Ⓚ]	3"	25	71
208 [Ⓚ]	3 1/2"	10	120
209 [Ⓚ]	4"	10	130

[Ⓚ] Not UL Listed.

Thin wall conduit fittings (for EMT conduit)

Nailing straps – steel

EMT fittings

NAILING STRAPS – CAST STEEL

Applications:

- To secure EMT conduit, flexible metallic conduit, armoured cable and metal-clad cable to mounting surface

Standard material:

- Cast steel

Standard finish:


- Zinc plated



Cat. #	Conduit sizes		Unit qty.	Wt. lbs. per 100	Load rating
	EMT	Rigid			
NS 1	1/2"	3/8"	100	2	25lb.
NS 2	3/4"	1/2"	100	2	30lb.
NS 3	1"	3/4"	100	3	40lb.

Dimensions (in inches):

Cat. #	A	B	C	D
NS 1	3/16	1	1 7/8	3/4
NS 2	3/4	1 1/4	2	15/16
NS 3	3/16	1 1/2	2 1/2	1 1/8



NAILING STRAPS – STAMPED STEEL

Applications:

- To secure EMT conduit

Certifications and compliances:

- UL File No. E-184283

Standard material:

- Pre-galvanized stamped steel



Cat. #	Conduit sizes		Unit Qty.	Wt. lbs. per 100
	EMT	Rigid		
NSS1	1/2"	3/8"	100	2
NSS2	3/4"	1/2"	100	2
NSS3	1"	3/4"	100	3

Dimensions (in inches):

Cat. #	A	B	C	Radius
NSS1	2.100	1.040	0.080	0.350
NSS2	2.300	1.275	0.080	0.460
NSS3	2.200	1.500	0.080	0.580

