

Eaton H-Max variable frequency drive

HMX32AG07522-N

UPC:786685473604

Dimensions:

- **Height:** 25.98 IN
- **Length:** 10.49 IN
- **Width:** 9.06 IN

Weight:82.6 LB

Notes:All boards are varnished. Corrosion resistant.
Battery included in all drives for real-time clock.
Keypad kit includes HOA bypass. Keypad kit includes HOA, back reset for Europe application.
EMI/RFI filters included. DC link choke included.

Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Brake Chopper:** No brake chopper
- **Input:** EMC C2
- **Keypad:** Graphical panel
- **Amperage Rating:** 75A
- **Enclosure:** Open NEMA Type 2 IP54
- **Frame Size:** FR7
- **Horsepower:** 25 hp
- **Phase:** Three-phase
- **Software:** A
- **Voltage Rating:** 200-240 V

Supporting documents:

- [Variable frequency drive - Product overview](#)
- [Eatons Volume 6-Solid-State Motor Control](#)
- [HMX_\(FR7\) 3D Inventor](#)
- [HMX_\(FR7\) AutoCAD 2D Footprint](#)



- [HMX_\(FR7\) AutoCAD 2D Footprint \(mm\)](#)
- [HMX_\(FR7\) 2D Drawing Xchange](#)
- [HMX_\(FR7\)2D PDF](#)
- [HMX_\(FR7\) 3D Model Xchange](#)
- [H-Max Series Adjustable Frequency Drive Installation Manual](#)
- [Eaton H-Max HVAC Drives](#)
- [Eaton Specification Sheet - HMX32AG07522-N](#)

Certifications:

- IEC 61800-5-1
- cUL Certified
- UL 508C
- EN 61800-5-1

Product compliance:

- CE Marked