




Eaton FlexPDU and Maintenance Bypass PDU

Eaton provides five different functions for rack power distribution solutions. Two of these functions, FlexPDU and Maintenance Bypass PDU, were created as accessories specific to some of our UPSs. Both of these units offer the flexibility of connections to meet the demanding requirements of today's data center architects.

The HotSwap Maintenance Bypass (MBP) unit enables easy UPS replacement without interruption of the load. The HotSwap MBP is ideal when exchanging a unit or servicing a UPS. For added convenience, the HotSwap MBP offers two types of receptacles: 5-15R or 5-20R.

The FlexPDU is a basic function power distribution unit with a short power cord for easy, close mounting. FlexPDUs are available with 5-15R, 5-20R or L5-20R output receptacles, for connection to a wide range of equipment.

Both of these options allow for easy deployment, even in space-constrained environments. You have a variety of mounting options, including top and side mounting.

Features

- HotSwap MBP provides service continuity during UPS maintenance or upgrade
- Both units offer connections to all types of equipment
- Eases installation with flexible mounting options
- Minimal depth accommodates most space constraints



Side mounting Flex PDU
with Tower UPS



Top mounting horizontal
FlexPDU with 2U UPS



HotSwap MBPs rackmounted
horizontally in rack



Top mounting vertical
FlexPDU



Powering Business Worldwide

FLEXPDU MODELS

Catalog number	Style Number	Input Plug	Breaker	Max kW	Function	Cord (ft)	Orientation	Receptacles	Dimensions (H x W x D, in)
EFLXL1500R-PDU1U	58015	5-15P	None	1.44	BA	3	1U	(12) 5-15R	1.7 x 19.0 x 2.4
EFLXL2000R-PDU1U	58020	5-20P	None	1.92	BA	3	1U	(12) 5-20R	1.7 x 19.0 x 2.4
EFLXL2000R-PDU1UL	58021	5-20P	None	1.92	BA	3	1U	(5) L5-20R	1.7 x 19.0 x 3.0
EFLXI3000R-PDU1UIEC	68438	C20 Inlet	(2) 20A	3.33	BA	3	1U	(12) C13, (1) C19	1.7 x 19.0 x 2.4

HOTSWAP MODELS

Catalog number	Style Number	Input Plug	Breaker	Max kW	Function	Cord (ft)	Orientation	Receptacles	Dimensions (H x W x D, in)
EHBPL1500R-PDU1U	58115	5-15P	None	1.44	BA	8	2U	(6) 5-15R	2.1 x 17.3 x 3.8
EHBPL2000R-PDU1U	58120	5-20P	None	1.92	BA	8	2U	(6) 5-20R	2.1 x 17.3 x 3.8
EHBPL3000R-PDU1U	58130	L5-30P	(2) 20A	2.88	BA	3.3	2U	(5) 5-20R	2.1 x 17.3 x 3.8

COMPATIBILITY MATRIX FOR RACKMOUNT UPSs*

FlexPDU plug/amp rating	UPS model (North American only)	Rack mounting
15A	Eaton 5P 1U UPS, 550, 750, 1000 and 1500 VA	✓
	Eaton 5P 2U UPS, 1500, 2200 and 3000 VA	✓
	Eaton 5) 2U Compact UPS, 750, 1000 and 1500 VA	✓
	Eaton 5PX UPS, 1000 and 1500 VA	✓
	Eaton 9PX UPS, 700, 1000 and 1500 VA	✓
20A	Eaton 5PX UPS, 2200 VA	✓
	Eaton 9PX UPS, 2000 VA	✓

*For tower models, all FlexPDUs can be wall-mounted. **Rear mounting available on 3U models only.

HotSwap MBP plug/amp rating	UPS model (North American only)	Rack mounting
15A	Eaton 5P UPS, 550, 750, 1000 and 1500 VA	✓
	Eaton 5P 2U UPS, 1500, 2200 and 3000 VA	✓
	Eaton 5P 2U Compact UPS, 750, 1000 and 1500 VA	✓
	Eaton 5PX UPS, 1000 and 1500 VA	✓
	Eaton 9PX UPS, 700, 1000 and 1500 VA	✓
20A	Eaton 5PX UPS, 2200 VA	✓
	Eaton 9PX UPS, 2000 VA	✓
30A	Eaton 5PX UPS, 3000 VA	✓
	Eaton 9PX UPS, 3000 VA	✓

*For tower models, all HotSwap MBPs can be wall-mounted. **Rear mounting available on 3U models only.

To interact with the FlexPDU and Maintenance Bypass PDF, please visit: [Eaton.com/epdu](https://www.eaton.com/epdu)

Eaton
1000 Eaton Boulevard
Cleveland, OH 44122
United States
Eaton.com

©2017 Eaton
All Rights Reserved
Printed in USA
Publication No. PDU17FXA / GG
August 2017

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.

