# ES sealing hubs and TSC epoxy sealing compound

Cl. I, Div. 1 & 2, Groups C, D Cl. II, Div. 1 & 2, Groups E, F, G Explosionproof Watertight

### **Applications:**

ES sealing hubs are used to:

- · Seal vertical conduit risers at switchgear and motor control centers, sheet metal structures or cast boxes and enclosures
- Seal horizontal conduit runs at enclosures when used with TSC sealing compound

## Certifications and Compliances:

- Class I, Divisions 1 & 2, Groups C, D
- Class II, Divisions 1 & 2, Groups E, F, G
- UL standard: UL1203
- CSA standard: C22.2 No. 30

#### Standard material:

· Feraloy iron alloy

#### Standard finish:

Electrogalvanized



## **Ordering information:**

Female hub size	Male hub size	Cat. #	internal volume in cubic inches
1/2"	1″	ES31	0.65
3/4"	1"	ES32	0.65
1"	11/2"	ES53	3.20
11/4"	2"	ES64	4.90
11/2"	2"	ES65	4.70
2"	21/2"	ES76	9.10
3"	4"	ES108	36.00
4"	5"	ES01210	95.00
5"	6"	ES014012	155.00

Note: Order SG sealing gasket and locknut separately.

## TSC epoxy sealing compound




A two-part epoxy sealing compound may be used to seal ES sealing hubs. It is quick and easy to measure, mix and install. The compound is kneaded until a uniform color is obtained. It is then packed around the conductors to effectively seal the cable.


## Ordering information:

Standard carton qty.	Tube size	Cat. #Ø
10	0.5 oz.	TSC05
10	1.0 oz.	TSC1
5	4.0 oz.	TSC4


## Typical installations:



- 1. ES sealing hub
- 2. EJB junction box
- 3. UNY union
- 4. EDS factory sealed control station
- 5. EYS horizontal seal
- 6. Explosionproof motor




- 1. ES sealing hub
- 2. LT connector
- 3. Locknut
- 4. Sealing gasket
- 5. Junction box
- 6. UNY union
- 7. Synchronous motor
- 8. EDS factory sealed control station
- 9. LT conduit



- 1. ES sealing hub
- 2. Locknut
- 3. Sealing gasket
- 4. Sheet metal structure, motor control center, panelboard, unit sub-station, etc.

# **Dimensions (in inches):**



Cat. #	а	b	C	d	е
ES31	19/16	7/8	2	31/32	11/4
ES32	113/16	7/8	2	15/16	11/2
ES53	21/4	13/8	31/16	1 15/16	13/4
ES64	23/4	13/4	31/8	1 15/16	23/16
ES65	23/4	15/8	35/32	2	27/16
ES76	31/2	21/16	311/16	2	3
ES108	5 <sup>1</sup> / <sub>4</sub>	35/8	413/16	231/32	41/4
ES01210	65/8	43/4	625/32	4 <sup>27</sup> / <sub>32</sub>	51/4
ES014012	71/4	525/32	73/8	511/32	61/2

Sealing hubs are approved for use in hazardous locations when Chico X fiber and Chico A sealing compound are used to make the seal. Sealing hubs are approved for horizontal conduit runs for use in hazardous locations when used with TSC sealing compound - order 1 oz. tube as TSC1

Order quantity of one (1) TSC05 or TSC1 equals ten (10) tubes; one (1) TSC4 equals five (5) 4.0 oz. tubes.

