

## Eaton molded case circuit breaker accessory handle mechanism

**47A4446G36**

**UPC:**786679651803

### **Dimensions:**

- **Height:** .7 IN
- **Length:** 8.7 IN
- **Width:** 6 IN

**Weight:**.5 LB

### **Warranties:**

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

### **Specifications:**

- **Type:** Disconnect switch shaft
- **Amperage Rating:** 30, 60, 100, 200A
- **Series:** Series C
- **Shaft Length:** 6.5 in

### **Supporting documents:**

- [Application of Tap Rules to Molded Case Breaker Terminals](#)
- [UL listed 100%-rated molded case circuit breakers](#)
- [Application of Multi-Wire Terminals for Molded Case Circuit Breakers](#)
- [Plug-in adapters for molded case circuit breakers product aid](#)
- [Power metering and monitoring with Modbus RTU product aid](#)
- [Motor protection circuit breakers product aid](#)
- [Multi-wire lugs product aid](#)
- [Circuit breaker motor operators product aid](#)

- [StrandAble terminals product aid](#)
- [Current limiting Series C molded case circuit breakers product aid](#)
- [Eatons Volume 12-Aftermarket, Renewal Parts and Life Extension Solutions](#)
- [Molded case circuit breakers](#)
- [Breaker service centers](#)
- [Series C G-Frame molded case circuit breakers time current curves](#)
- [Eaton Specification Sheet - 47A4446G36](#)
- [Series C F-Frame molded case circuit breakers](#)
- [MOEM MCCB product selection guide](#)
- [Series C J-Frame molded case circuit breakers time current curves](#)

**Certifications:** No Data

**Product compliance:**

- [Contact Manufacturer](#)