



Powering Business Worldwide

pe.eaton.com

Eaton 9355 UPS

KA1012200000010

UPC:743172018564

Dimensions:

- **Height:** 47.8 IN
- **Length:** 33.5 IN
- **Width:** 12 IN

Weight:609 LB

Notes:220V units are wye connected 220/127V input and 220/127V output, three-phase, four-wire plus ground.

Warranties:

- 1 year Service Protection Plan, 7 x 24 emergency response, On-site start-up support (8 hours/day, 5 days/week), 3 year battery warranty, 1 year eNotify remote monitoring

Specifications:

- **Type:** UPS
- **Topology:**
- **Enclosure:** Nema 1
- **Package Contents:** 1 ready-to-go UPS; Software Suite CD; User Guide
- **Efficiency:** 91%, typical
- **Phase (Input):** 127/220 VAC
- **Quantity:** 1
- **Nominal Frequency:** 75/130-144/249 VAC per phase
- **Input Frequency Range:** 45-65 Hz
- **Input Power Factor:** P.F >0.99 typical, >0.96 frequency converter
- **Output Waveform:** Sine Wave
- **Output Voltage Range:** $\pm 1\%$ static; $\pm 5\%$ dynamic at 100% resistive load change, <1 ms response time
- **Output Frequency:** 50/60 Hz



- **Battery Quantity:** 64
- **Battery Rating:** 9 Ah
- **Battery Type:** Sealed, lead-acid, maintenance-free
- **Extended Battery Capability:** Yes, via EBM
- **Communication:** (1) RS-232, (1) relay contact, (1) REPO, (2) environmental input
- **Expansion Slots:** (2) X-Slot communication bays
- **Ethernet Interface:** Yes, via Gateway card
- **Software Compatibility:** Bundled Software Suite CD
- **User Interface:** LCD Display with blue backlight

Supporting documents:

- [Eaton Specification Sheet - KA1012200000010](#)

Certifications:

- EN 50091-2 Class A
- UL Listed
- cUL Certified
- IEC 60950
- EN 62040-1-1
- UL 1778
- IEC 62040-1-1

Product compliance:

- ISO 9001
- ISO 14001