



Powering Business Worldwide

[pe.eaton.com](http://pe.eaton.com)

## Eaton Bussmann series fast-acting fuse

ABC-6

UPC:051712700061

### Dimensions:

- **Height:** 1.25 IN
- **Length:** .25 IN
- **Width:** .25 IN

**Weight:** .03 LB

**Notes:** Ceramic body allows for higher amp/volt rating combinations.

**Warranties:** No Data

### Specifications:

- **Type:** Electronic
- **Application:** Electronic circuits
- **Voltage Rating:** 250 Vac, 125 Vdc, 32 Vac (self certified)
- **Amperage Rating:** 6A
- **Interrupt Rating:** 200 AIC at 250 Vac, 10 kAIC at 125 Vac/dc
- **Connection:** Ferrule end X ferrule end
- **Material Type:** Ceramic tube, nickel-plated brass endcaps
- **Packaging Type:** Standard
- **Diameter:** .25 IN
- **Melting (L2T):** Typical pre-arc: 58
- **Resistance:** Typical DC cold: .021 ohms
- **Voltage Drop:** Typical: .19 mV
- **Fuse Indicator:** Non Indicating
- **Response Time:** 4 hr minimum at 100%, 60 min maximum at 135%, 120 s maximum at 200%

### Supporting documents:

- [ABC 6A BUSS FA 5-IN BOX](#)



**Certifications:** No Data

**Product compliance:**

- CE Marked

---

© 2016 Eaton. All rights reserved.