



# LED7WPAR20/NFL/830K-DIM-G4A



|                      |                                                                                   |
|----------------------|-----------------------------------------------------------------------------------|
| <b>Description</b>   | 3000K LED LiteSpan PAR20, Narrow Flood 25 Degree Beam, 7W - 470lm, Dimmable, 2BD, |
| <b>Ordering Code</b> | 90020                                                                             |
| <b>UNSPSC Code</b>   | 39112102                                                                          |

## Specifications

|                                     |                                  |
|-------------------------------------|----------------------------------|
| <b>Voltage Rating</b>               | 120                              |
| <b>Voltage Type</b>                 | AC/DC                            |
| <b>Watts</b>                        | 7                                |
| <b>Base Type</b>                    | Medium Screw (E26)               |
| <b>Bulb Type</b>                    | PAR 20                           |
| <b>MOL in/mm</b>                    | 3.37/85.5                        |
| <b>MOD in/mm</b>                    | 2.48/63                          |
| <b>Lumens</b>                       | 500                              |
| <b>CT deg K</b>                     | 3000                             |
| <b>CRI</b>                          | 80                               |
| <b>Beam Angle</b>                   | 25                               |
| <b>Rated Life</b>                   | 25,000                           |
| <b>Replaces</b>                     | 55W Halogen                      |
| <b>Ambient Operating Temp Range</b> | -20° C (-4° F) to 40° C (104° F) |

[watch](#) > [like](#) > [follow](#)



selection. solutions. simplicity. [eiko.com](http://eiko.com)

23220 W. 84<sup>th</sup> St, Shawnee, KS 66227 • (P) 1.800.852.2217 (F) 1.800.492.8975  
Canada: 81 King St, Barrie, ON L4N 6B5 • (P) 1.888.410.8151 (F) 1.888.705.1335