

LED A15 & A19



A15
E26

A19
E26



A19
GU24



A15 Colored
E26

5-15
watts

replaces
40-100W
incan

GU24
or E26
base

240°/
300°
beam

Features

- Direct replacement for 40, 60, 75, 100W incandescent A lamps
- 300° Omni beam angle is ideal for table lamps, wall sconces, and luminous globe fixtures
- 80% more efficient and 30x longer life than standard incandescent
- Smooth, clean outside housing
- Compatible with a wide array of dimmers
- Comfortable diffused light
- Instant-On with no warm up, unlike CFLs
- Available in 2700K, 3000K, 4000K and 5000K
- Shatter resistant for reduced risk of injury and breakage

RoHS
Compliant

cUL US LISTED



Performance

- 6W replaces 40W incandescent
- 8/9/9.5W replaces 60W incandescent
- 11W replaces 75W incandescent
- 15W replaces 100W incandescent
- 120V @ 60Hz
- Standard series 80+ CRI for enhanced color and lighting uniformity from lamp to lamp
- ANSI construction compliant
- Suitable for damp locations
- 50,000 hour design life
- Select items enclosed fixture rated
- Not for use with electronic timers, photocells, or motion/occupancy sensors
- Contains no mercury or lead; classified as non-hazardous waste
- -20° C (-4° F) to 40° C (104° F) operating temperature

Applications

- Restaurants & Hospitality
- Retail
- Residential
- Accent/Display Lighting
- Healthcare



selection. solutions. simplicity. eiko.com

LED A15 & A19

Dimensions



	Order Code	Item #	W	Lm	CCT	CRI	Bm	MOL	MOD	Life/Hrs	Replaces Incandescent	ES
A15 E26	09976	LED5WA15/OMN/BLUE-G8	5W	-	Blue	-	300°	3.58"	1.89"	10K	-	
	09981	LED5WA15/OMN/RED-G8	5W	-	Red	-	300°	3.58"	1.89"	10K	-	
	09973	LED5WA15/OMN/YELLOW-G8*	5W	-	Yellow	-	300°	3.58"	1.89"	10K	-	
	10057	LED8WA15/OMN/827-DIM-G8*	8W	800	2700K	80+	240°	3.49"	1.97"	25K	60W A15	★
	10058	LED8WA15/OMN/830-DIM-G8*	8W	800	3000K	80+	240°	3.49"	1.97"	25K	60W A15	★
A19 E26	10059	LED8WA15/OMN/840-DIM-G8*	8W	800	4000K	80+	240°	3.49"	1.97"	25K	60W A15	★
	09882	LED6WA19/OMN/827-DIM-G8*	6W	480	2700K	80+	300°	4.21"	2.36"	25K	40W A19	★
	09887	LED6WA19/OMN/827-G8*	6W	480	2700K	80+	300°	4.33"	2.36"	25K	40W A19	★
	09750	LED6WA19/OMN/830-G8*	6W	480	3000K	80+	300°	4.33"	2.36"	25K	40W A19	★
	09751	LED6WA19/OMN/840-G8*	6W	480	4000K	80+	300°	4.33"	2.36"	25K	40W A19	★
	09748	LED6WA19/OMN/830-DIM-G8*	6W	480	3000K	80+	300°	4.33"	2.36"	25K	40W A19	★
	09749	LED6WA19/OMN/840-DIM-G8*	6W	480	4000K	80+	300°	4.33"	2.36"	25K	40W A19	★
	09895	LED9WA19/OMN/827-DIM-G8*	9W	800	2700K	80+	300°	4.21"	2.36"	25K	60W A19	★
	09896	LED9WA19/OMN/830-DIM-G8*	9W	800	3000K	80+	300°	4.21"	2.36"	25K	60W A19	★
	09752	LED9WA19/OMN/840-DIM-G8*	9W	800	4000K	80+	300°	4.21"	2.36"	25K	60W A19	★
	10060	LED9WA19/OMN/850-DIM-G8*	9W	800	5000K	80+	300°	4.21"	2.36"	25K	60W A19	★
	09889	LED9.5WA19/OMN/827-G8*	9.5W	800	2700K	80+	300°	4.33"	2.36"	25K	60W A19	★
	09753	LED9.5WA19/OMN/830-G8*	9.5W	800	3000K	80+	300°	4.33"	2.36"	25K	60W A19	★
	09941	LED9.5WA19/OMN/840-G8*	9.5W	800	4000K	80+	300°	4.33"	2.36"	25K	60W A19	★
	09885	LED11WA19/OMN/827-DIM-G8*	11W	1,100	2700K	80+	300°	4.33"	2.36"	25K	75W A19	★
	09942	LED11WA19/OMN/830-DIM-G8*	11W	1,100	3000K	80+	300°	4.33"	2.36"	25K	75W A19	★
	09943	LED11WA19/OMN/840-DIM-G8*	11W	1,100	4000K	80+	300°	4.33"	2.36"	25K	75W A19	★
	10061	LED11WA19/OMN/850-DIM-G8*	11W	1,100	5000K	80+	300°	4.33"	2.36"	25K	75W A19	★
	09886	LED15WA19/OMN/827-DIM-G8*	15W	1,600	2700K	80+	300°	4.33"	2.36"	25K	100W A19	★
	09944	LED15WA19/OMN/830-DIM-G8*	15W	1,600	3000K	80+	300°	4.33"	2.36"	25K	100W A19	★
	09945	LED15WA19/OMN/840-DIM-G8*	15W	1,600	4000K	80+	300°	4.33"	2.36"	25K	100W A19	★
GU24	09946	LED15WA19/OMN/850-DIM-G8*	15W	1,600	5000K	80+	300°	4.33"	2.36"	25K	100W A19	★
	09974	LED9WA19/OMN/827-GU24-DIM-G8	9W	800	2700K	80+	300°	4.25"	2.36"	25K	60W A19	★
	09975	LED9WA19/OMN/830-GU24-DIM-G8	9W	800	3000K	80+	300°	4.25"	2.36"	25K	60W A19	★
	10108	LED9WA19/OMN/840-GU24-DIM-G8	9W	800	4000K	80+	300°	4.25"	2.36"	25K	60W A19	★
	10122	LED11WA19/OMN/827-GU24-DIM-G8	11W	1,100	2700K	80+	300°	4.25"	2.36"	15K	75W A19	★
	10014	LED11WA19/OMN/830-GU24-DIM-G8	11W	1,100	3000K	80+	300°	4.25"	2.36"	15K	75W A19	★
	10100	LED11WA19/OMN/840-GU24-DIM-G8	11W	1,100	4000K	80+	300°	4.25"	2.36"	15K	75W A19	★
	10124	LED15WA19/OMN/827-GU24-DIM-G8	15W	1,600	2700K	80+	300°	4.25"	2.36"	15K	75W A19	★
	10125	LED15WA19/OMN/830-GU24-DIM-G8	15W	1,600	3000K	80+	300°	4.25"	2.36"	15K	75W A19	★
	10126	LED15WA19/OMN/840-GU24-DIM-G8	15W	1,600	4000K	80+	300°	4.25"	2.36"	15K	75W A19	★

NOTE: Use order code when ordering.

*Enclosed fixture rated

watch > like > follow



23220 W. 84th St, Shawnee, KS 66227 · (P) 1.800.852.2217 · (F) 1.800.492.8975
 Canada: 81 King St, Barrie, ON L4N 6B5 · (P) 1.888.410.8151 · (F) 1.888.705.1335