

LNC2

SMALL LED LITEPAK

FEATURES

- 60% more lumens and increased performance than smaller LNC models
- 3000K, 4000K and 5000K as well as Amber
- Type II, III and IV distributions available for a variety of application needs
- Quick-mount adapter allows easy installation/maintenance
- 347V and 480V versions for industrial applications and Canada
- Stock versions available for fast service
- Full cut-off, neighbor friendly, IDA approved
- Optional photocontrol for additional energy savings



CONTROL TECHNOLOGY



SPECIFICATIONS

CONSTRUCTION

- Rugged die-cast aluminum housing protects components and provides an architectural appearance
- Casting thermally conducts LED heat to optimize performance and long life
- Powder paint finish provides durability in outdoor environments

OPTICS

- Zero uplight distributions using individual acrylic
- LED optics provide IES type II, III and IV distributions. Optional (CS) acrylic diffuser available for reduced glare
- Prismatic refractor lens provides ~10% uplight for increased vertical footcandles and forward light projection ideal for security lighting
- L96 at 60,000hrs (Projected per IESNA TM-21-11), see table on page 3 for all values

INSTALLATION

- Quick-mount adapter provides easy installation to wall or to recessed junction boxes (4" square junction box)
- Designed for direct j-box mount.
- Optional 1/2" conduit hubs available (standard for sensor, SiteSync and battery versions)

ELECTRICAL

- 120V-277V universal voltage 50/60Hz 0-10V dimming drivers
- 347V and 480V dimmable driver option in 12L-070 configuration
- Minimum operating temperature is -40°C/-40°F (excludes 12L-035 and P15 configurations)
- Drivers have greater than .90 power factor and less than 20% Total Harmonic Distortion
- Driver RoHS and IP66
- 10kA surge protector
- 3000K CCT nominal, 4000K CCT nominal, 5000K CCT nominal (70 CRI)
- 9, 12 and 18 LED configurations available see pages 2 and 3 for electrical and photometric details

CONTROLS

- Universal button photocontrol
- Occupancy sensor options available for complete on/off and dimming control
- SiteSync pre-commissioned wireless controls (with or without sensor)
- Integral Battery Backup provides emergency lighting for the required 90 minute path of egress
- Dual Driver and Dual Power Feed option for 18L-070 versions

CERTIFICATIONS

- DLC® DesignLights Consortium Qualified, with some Premium Qualified configurations. Please refer to the DLC website for specific product qualifications at www.designlights.org
- Listed to UL1598 and CSAC22.2#250.0-24 for wet locations
- Made-to-order versions are IP-65 rated
- This product qualifies as a "designated country construction material" per FAR 52.225-11 Buy American-Construction Materials under Trade Agreements effective 04/23/2020. See Buy American Solutions

WARRANTY

- 5 year limited warranty
- See HLI Standard Warranty for additional information

KEY DATA	
Lumen Range	2600–4100
Wattage Range	29–42
Efficacy Range (LPW)	85–112
Fixture Projected Life (Hours)	L96>60K
Weights lbs. (kg)	9.6 (24.5)

DATE: _____ LOCATION: _____

TYPE: _____ PROJECT: _____

CATALOG #: _____



*Shown with CS acrylic diffuser

RELATED PRODUCTS

θ [LNC](#)

θ [INC3](#)

θ [LNC4](#)

DATE:	LOCATION:
TYPE:	PROJECT:
CATALOG #:	

LNC2

SMALL LED LITEPAK

ORDERING GUIDE

Example: LNC2-9L-3K-2-U-DBT-PCU

CATALOG #

ORDERING INFORMATION

Series	# LEDs	CCT/CRI	Drive Current	IES Distribution	Voltage	Mounting
LNC2 Small LitePak LNC2	9L 9 LEDs 12L 12 LEDs 18L 18 LEDs P15 15w Prismatic Refractor P25 25w Prismatic Refractor P35 35w Prismatic Refractor	3K 3000K nominal, 70 CRI 4K 4000K nominal, 70 CRI 5K 5000K nominal, 70 CRI AM Amber ⁹	070 700mA 035 350mA (12L & 18L only)	2 Type II ¹ 3 Type III ¹ 4 Type IV ¹ FT Forward Throw (Prismatic Refractor only)	U 120-277V 1 120V 2 208V 3 240V 4 277V 5 480V ⁸ F 347V ⁸	Leave blank for down position NV Inverted ²

Finish	Control Options	Options
BLT Black Matte Textured BLS Black Gloss Smooth DBT Dark Bronze Matte Textured DBS Dark Brone Gloss Smooth GTT Graphite Matte Textured LGS Light Grey Gloss Smooth PSS Platinum Silver Smooth WHT White Matte Textured WHS White Gloss Smooth VG Verde Green Textured Color Option CC Custom Color	SCP Occupancy Sensor Programmable (Dim) ^{4,5} PCU Universal Button Photocontrol SWP SiteSync Pre-Commission ⁶ SWPM SiteSync Pre-commission w/ OCC Sensor ^{6,7} Specify SCP Height 8F Up to 8ft mount height 20F Up to 20ft mount height	EH Battery Backup Unit with Heater (-30°C) ³ E Battery Backup Unit (0°C) ³ F Fuse & Fuse-Holder (not available with Battery Backup) ³ CS Comfort Shield (N/A with Prismatic Refractor) 2DR Dual Driver (18L - 700mA only) 2PF Dual Power Feed (18L - 700mA only) CH Surface Conduit Hubs

Notes:

- IES distributions only available with 9L, 12L, and 18L versions
- Not available with occupancy sensor, battery backup or prismatic refractor options
- Must specify voltage (120 or 277 only for E & EH)
- Must order minimum of one remote control to program dimming settings, 0-10V fully adjustable dimming with automatic daylight calibration and different time delay settings, 120-277V only
- PCU option not applicable, included in sensor
- 18L - 700mA versions only. Not available with 2DR or 2PF options. Must specify group and zone information at time of order
- Specify time delay; dimming level and mounting height
- 12L - 700mA version only

STOCK ORDERING INFORMATION

Catalog Number	Lumens	Wattage	Distribution	CCT/CRI	Voltage	Distribution	Weight lbs. (kg)	Finish	Options
LNC2-12LU-4K-3-DB	2,662	29W	3	4000K/70CRI	120-277V	Type 3	7.0 (13.3)	Bronze	*
LNC2-12LU-5K-3-DB	2,868	29W	3	5000K/70CRI	120-277V	Type 3	7.0 (13.3)	Bronze	*
LNC2-12LU-5K-3-DB-PC-U	2,868	29W	3	5000K/70CRI	120-277V	Type 3	7.0 (13.3)	Bronze	Photocell *
LNC2-18LU-4K-3-DB	3,806	42W	3	4000K/70CRI	120-277V	Type 3	7.0 (13.3)	Bronze	*
LNC2-18LU-5K-3-DB	4,106	42W	3	5000K/70CRI	120-277V	Type 3	7.0 (13.3)	Bronze	*
LNC2-18LU-5K-3-DB-PC-U	4,106	42W	3	5000K/70CRI	120-277V	Type 3	7.0 (13.3)	Bronze	Photocell *
LNC2-P35-4K-PCU	4,025	37W	FT	4000K/70CRI	120-277V	FT	7.0 (13.3)	Bronze	Photocell
LNC2-P35-PCU	4,108	37W	FT	5000K/70CRI	120-277V	FT	7.0 (13.3)	Bronze	Photocell

REPLACEMENT PART - MADE TO ORDER

Catalog Number	Description
☐ SCP-Remote	Remote control for SCP option. Order at least one per project to program and control fixtures*

Notes:

- * IES distributions only available with 9L, 12L and 18L versions

LNC2

SMALL LED LITEPAK

PERFORMANCE DATA

STANDARD 9, 12 AND 18L VERSIONS

# Of LEDs	Nominal Wattage	System Watts	Dist. Type	5K (5000K NOMINAL 70 CRI)					4K (4000K NOMINAL 70 CRI)					3K (3000K NOMINAL 80 CRI)				
				Lumens	LPW*	B	U	G	Lumens	LPW*	B	U	G	Lumens	LPW*	B	U	G
9	700mA	21W	2	2,083	97	1	0	1	2,072	97	1	0	1	1,927	90	1	0	1
			3	1,972	92	0	0	1	1,962	92	0	0	1	1,825	85	0	0	1
			4	2,097	98	0	0	1	2,087	98	0	0	1	1,941	91	0	0	1
12	350mA	14W	2	1,513	110	0	0	1	1,506	109	0	0	1	1,440	104	0	0	1
			3	1,433	104	0	0	1	1,426	103	0	0	1	1,364	99	0	0	1
			4	1,524	110	0	0	1	1,543	112	0	0	1	1,476	107	0	0	1
	700mA	29W	2	2,777	97	1	0	1	2,763	97	1	0	1	2,570	90	1	0	1
			3	2,629	92	1	0	1	2,616	91	1	0	1	2,433	85	1	0	1
			4	2,797	98	1	0	1	2,783	97	1	0	1	2,588	90	1	0	1
18	350mA	21W	2	2,270	107	1	0	1	2,259	106	1	0	1	2,074	97	1	0	1
			3	2,149	101	0	0	1	2,138	100	0	0	1	1,963	92	0	0	1
			4	2,286	107	0	0	1	2,275	107	0	0	1	2,125	100	0	0	1
	700mA	43W	2	4,261	99	1	0	1	4,240	98	1	0	1	3,943	91	1	0	1
			3	4,033	93	1	0	1	4,014	93	1	0	1	3,733	86	1	0	1
			4	4,290	99	1	0	1	4,270	99	1	0	1	3,971	92	1	0	1

PRISMATIC REFRACTOR

# Of LEDs	Nominal Wattage	Dist. Type	5K (5000K NOMINAL 70 CRI)					4K (4000K NOMINAL 70 CRI)					3K (3000K NOMINAL 80 CRI)				
			Lumens	LPW*	B	U	G	Lumens	LPW*	B	U	G	Lumens	LPW*	B	U	G
1	15W	FT	1,741	132	0	3	2	1,706	129	0	3	2	1,648	125	0	3	2
	25W		2,929	117	1	3	2	2,806	112	1	3	2	2,773	111	1	3	2
	35W		4,108	112	1	3	3	4,025	110	1	3	3	3,889	106	1	3	3

Notes:
 * Lumens values are from photometric tests performed in accordance with IESNA LM-79-08. Data is considered to be representative of the configurations shown. Actual performance may differ as a result of end-user environment and application. LNC2-12L battery mode produces 1,546 initial lumens. Meets UL924 90 minute discharge pattern.

PROJECTED LUMEN MAINTENANCE

STANDARD 9, 12 AND 18L VERSIONS

Ambient Temperature	OPERATING HOURS					
	0	25,000	50,000	TM-21-11* L96 60,000	100,000	L70 (Hours)
25°C / 77°F	1.00	0.98	0.97	0.96	0.95	>791,000
40°C / 104°F	0.99	0.98	0.96	0.96	0.95	>635,000

PRISMATIC REFRACTOR

Ambient Temperature	OPERATING HOURS					
	0	25,000	50,000	TM-21-11* L96 60,000	100,000	L70 (Hours)
25°C / 77°F	1.00	0.94	0.89	0.87	0.80	>160,000
40°C / 104°F	0.99	0.93	0.88	0.86	0.78	>150,000

* Projected per IESNA TM-21-11 * (Nichia 219B, 700mA, 85°C Ts, 10,000hrs). Data references the extrapolated performance projections for the LNC-12LU-5K base model in a 40°C ambient, based on 10,000 hours of LED testing per IESNA LM-80-08.

LNC2

SMALL LED LITEPAK

ELECTRICAL DATA

STANDARD 9, 12 AND 18L VERSIONS

# OF LEDS	Drive Current (mA)	Input Voltage (V)	Oper. Current (Amps)	System Power (W)
9	700mA	120	0.18	21
		277	0.08	21
12	350mA	120	0.12	14
		277	0.05	14
	700mA	120	0.24	29
		277	0.10	29
		347	0.08	29
		480	0.06	29
18	350mA	120	0.18	21
		277	0.08	21
	700mA	120	0.36	43
		277	0.16	43

PRISMATIC REFRACTOR

# OF LEDS	Drive Current (mA)	Input Voltage (V)	Oper. Current (Amps)	System Power (W)
1	350mA	120	0.11	13
		277	0.05	13
	600mA	120	0.21	25
		277	0.09	25
	900mA	120	0.31	37
		277	0.13	37


LUMINAIRE AMBIENT TEMPERATURE FACTOR (LATF)

Standard 9, 12, 18L and Prismatic Versions

Ambient Temperature		Lumen Multiplier
0° C	32° F	1.02
10° C	50° F	1.01
20° C	68° F	1.00
25° C	77° F	1.00
30° C	86° F	1.00
40° C	104° F	0.99
50° C	122° F	0.98

Use these factors to determine relative lumen output for average ambient temperatures from 0-40°C (32-104°F).

DIMENSIONS



LNC2

SMALL LED LITEPAK

DATE:	LOCATION:
TYPE:	PROJECT:
CATALOG #:	

ADDITIONAL INFORMATION

SHIPPING INFORMATION

Catalog Number	G.W(kg)/ CTN	Carton Dimensions			Carton Qty. per Master Pack
		Length Inch (cm)	Width Inch (cm)	Height Inch (cm)	
LNC2-12LU	14.3 (6.5)	14.5 (37)	11.4 (29)	8.4 (21.5)	2
LNC2-18LU	14.8 (6.7)	14.9 (38)	11.4 (29)	8.4 (21.5)	2

NV - INVERTED MOUNTING OPTIONS



*Requires Factory Installed Lens Option


Inverted mounting capabilities for uplighting applications. Specially designed frosted acrylic diffuser option softens output, improves uniformity and protects LED lenses.

SCP - PROGRAMMABLE OCCUPANCY SENSOR




Sensor offers greater control and energy savings with SCP programmable sensor with adjustable delay and dimming levels (Factory default is 10%) Visit: <http://www.hubbellighting.com/solutions/controls/> for control application information

SWP & SWPM - SITESYNC™



When ordering a fixture with the SiteSync lighting control option, additional information will be required to complete the order. The SiteSync Commissioning Form or alternate schedule information must be completed. This form includes Project locations Group information, and Operating schedules. For more detailed information please visit www.HubbellLighting.com/products/sitesync or contact Hubbell Lighting tech support at (800) 345-4928.

LNC2 - BATTERY BACK UP



11' Mounting Height

Provides Life Safety Code average illuminance of 1.0 fc. Assumes open space with no obstructions and mounting height of 11'.

Diagrams for illustration purposes only, please consult factory for application layout.

Battery backup units consume 6 watts when charging a dead battery and 2 watts during maintenance charging. EH (units with a heater) consume up to an additional 8 watts when charging if the battery temp is lower than 10°C

E & EH EMERGENCY BATTERY BACKUP



Standard versions utilize 9, 12 or 18 High Power LEDs to generate 1,600 - 4,200 lumens in Normal Mode and use 4 LEDs for up to 700 lumens in Emergency Mode. Prismatic refractor versions utilize 1 COB LED to generate approximately 900 lumens in emergency mode.

USE OF TRADEMARKS AND TRADE NAMES

All product and company names, logos and product identifies are trademarks ™ or registered trademarks ® of Hubbell Lighting, Inc. or their respective owners. Use of them does not necessarily imply any affiliation with or endorsement by such respective owners.