FLEXIBLE METAL STRAIGHT SQUEEZE CONNECTORS

Straight Squeeze Connectors, Insulated Malleable Iron
N/A **B61**



Catalog #: 3308

APPLICATIONS

For use in dry locations to bond flexible metal conduit to a box or enclosure
N/A

PRODUCT FEATURES

All malleable iron construction insures mechanical protection for the raceway
Electro zinc plated for added corrosion protection
UPC bar coded fittings are individually polybagged with a preprinted UPC-A bar code, and packaged in pre-scored tear top cartons for an attractive presentation

CULUS

UL Listed E195969

GENERAL PRODUCT INFORMATION

Trade Size:	2 in.

DRAWING DIMENSIONS

Dimension A:	2-3/4 in.
Dimension B:	45/64 in.
Thread Spec. B:	2 in. - 11-1/2 NPT
Dimension C:	1.930 in.
Dimension D:	2.450 MAX
Dimension E:	3-11/32 in.

PACKAGING

Package Type:	Carton
Ship Carton Qty.:	10
Product UPC-A Labeled:	No
Weight (Lbs. Per/C):	108.20
Ship Carton Length (in.):	8.13
Ship Carton Width (in.):	7.13
Ship Carton Height (in.):	6.94
Ctn Weight (Lbs.):	10.82
UPC Number:	050169033081
I2of5:	50050169033086