

# Ground Fault Products



## Commercial Grade, Portable GFCI Line Cords

### Circuit Guard® Portable GFCI Single Outlet, 15A 120V AC - 12/3 SJEOW

Description	Automatic Set.	Manual Set
2' (60.9 cm) GFCI line cord.	<b>GFP2CA</b>	<b>GFP2CM</b>
25' (762.0 cm) GFCI line cord.	<b>GFP25CA</b>	<b>GFP25CM</b>



### Circuit Guard® Portable GFCI Triple Tap Outlet, 15A 120V AC - 12/3 SJEOW

Description	Automatic Set.	Manual Set
2' (60.9 cm) GFCI line cord.	<b>GFP2TTA</b>	<b>GFP2TTM</b>
25' (762.0 cm) GFCI line cord.	<b>GFP25TTA</b>	<b>GFP25TTM</b>



### Circuit Guard® OEM Equipment Integrated Cord Sets, 15A 120V AC - 14/3 SJEOW

Description	Automatic Set.	Manual Set
15' (457.2 cm) GFCI with flying leads.	<b>GFP15LA</b>	<b>GFP15LM</b>
35' (1066.8 cm) GFCI with flying leads.	<b>GFP35LA</b>	<b>GFP35LM</b>



### 15A GFCI In Line GFCI, Single and Triple Tap, 15A 120V AC - 12/3 SJTW

Description	Automatic Set.	Manual Set
2' (60.9 cm), 5-15 single tap.	<b>GFPIL15125A</b>	<b>GFPIL15125M</b>
2' (60.9 cm), 5-15 triple tap.	<b>GFPIL15125TRIA</b>	<b>GFPIL15125TRIM</b>



### 20A GFCI In Line GFCI, Locking, 20A 120V AC - 12/3 SJTW

Description	Automatic Set.	Manual Set
2' (60.9 cm), L5-20 locking.	<b>GFPIL20125LKA</b>	<b>GFPIL20125LKM</b>

### 20A GFCI In Line GFCI, Locking, 20A 250V AC - 12/3 SJTW

Description	Automatic Set.	Manual Set
2' (60.9 cm), L6-20 locking.	<b>GFPIL20250LKA</b>	<b>GFPIL20250LKM</b>



## Specifications

### Portable GFCI Line Cords

Trip Level	4 to 6 mA.
Trip Time	.025 sec. nominal.
Frequency	60 Hz.
Voltage	120/250V AC +10% - 15%. Incorporates no voltage release feature.
Amperage	15A/20A.
Maximum Interrupting Capacity	2000A.
Operating Temperature	-35°C to 66°C or -30°F to 150°F.
Maximum Humidity	95%.
Housing	High-impact, UV stabilized PVC. UL 94V-0 flammability classification. Meets UL and CSA watertight requirements. Adhesive bonded.
Visual Fault Indication Light On	Indicates fault.
Listing and Standards	Meets UL943 Class A, UL File E41978, CSA Certified.
Codes	Meets all NEC® and CEC requirements.



NEC® is a registered trademark of the National Fire Protection Association (NFPA).