## Cable, Cord and Hose Reels



## Industrial Lighted Cord Reels, 50 Ft. (15.2m) - 16/3 AWG SJEO Cable



Cord End	Watts (Max)	Amps	Volts AC	Weight Lbs. (ka)	Catalog Number
LED hand lamp, with end light.	8 + 1	0.07	120	( 3)	HBL50162LED
Fluorescent hand lamp.	13	0.3	120	21 (9.5)	HBL50162FL
Incandescent hand lamp.	100	0.8	125	21 (9.5)	HBL50163IN

Note: Supplied with 5 ft. power supply cord with HBL5266C, 15A straight blade plug.

## **Accessories**



Watts Volts Weight Description (Max) AC Lbs. (kg) Catalog Number Amps Replacement stop. .2 (.09) **HBL16BS** Replacement LED hand lamp. 8 + 10.07 1 (.5) **HBL16LEDR\*** Replacement fluorescent hand lamp. 0.3 120 **HBL16FLR** 13 1 (.5) **HBL16INR** Replacement incandescent hand lamp. 100 0.8 125 1 (.5)

Note: \*ETL Listed by INTERTEK.

**HBLC25143IN** 



HBLC40182LED



**Commercial Lighted Cord Reels** 



Cable



Weight

HBLC40182AFL

HBLC40163FL

Description	Feet (m)	Cable Type	(Max)	Amps	Volts AC	Lbs. (kg)	Catalog Number
Reel with LED hand lamp, with flashlight end, white	40 (12.2)	#18/2 SJTOW	8 + 1	0.65	125	8.2 (3.7)	HBLC40182LED
Reel with non-metallic incandescent hand lamp and automatic shut off switch, yellow.	25 (7.6)	#16/3 SJT	75	0.6	125	9.0 (4.1)	HBLC25163AIN**
Reel with metallic incandescent hand lamp with receptacle, yellow.	25 (7.6)	#14/3 SJT	1,625	13	125	9.5 (4.3)	HBLC25143IN
Reel with fluorescent hand lamp and automatic shut off switch, white.	40 (12.2)	#18/2 SJTOW	13	0.3	120	8.2 (3.7)	HBLC40182AFL**
Reel with fluorescent hand lamp and in-line receptacle, white.	40 (12.2)	#16/3 SJT	1,200	10	120	9.0 (4.1)	HBLC40163FL

Watts

Note: \*\*Allows the electrical cord reel installation to conform to Article 511 of the National Electric Code concerning installation of electrical devices in commercial garages, repair facilities and storage locations by positioning the switch above the defined area where



[[]]. INTERTEK and the Intertek logo are registered trademarks of Intertek Group plc.

