

P3910 One-Light Close-To-Ceiling

Wall or ceiling mounted • Damp location listed



Description:

One-light LED flush mount with etched white opal acrylic diffuser. 3000K, 90+ CRI, 1,211 lumens. Acrylic bowl is attached with a twist and lock action. Can be mounted on ceiling or wall.

Specifications:

- Brushed Nickel (-09) (Plated)
- Steel construction
- White acrylic diffuser
- 120VA replaceable LED Module (part # 93053641)
- Etched white opal acrylic diffuser.
- Acrylic bowl is attached with a twist and lock action.
- Can be mounted on ceiling or wall.
- 1,211 lumens 71.2 lumens/watt
- 3000K color temperature, 90+ CRI
- Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
-

Performance:

Number of Modules	1
Input Power	17w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW	1211/71.2 (LM-79)
CCT	3000 K
CRI	90
Life (hours)	60,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15 Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30 °C
Warranty	5 year warranty
Labels	cCSAus Damp location listed

P3910-0930K9

Images:



Dimensions:

Diameter: 9"
Height: 4-3/8"

Glass
Width: 9"
Height: 3-3/8"

P3910 One-Light Close-To-Ceiling

Wall or ceiling mounted • Damp location listed



P3910-0930K9

Dimming Notes:

P3910 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron	Nova T	NTELV-300
Lutron	Vierti	VTELV-600
Lutron	Maestro	MAELV-600
Lutron	spacer/system	SPSELV-600
Leviton	Renoir II	AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.