



## Cables and Receptacles - Power Components

| Device Type                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Ratings                                                                                                                                                                      | Wires                                            | Conductor Colors**                                                                                                                           | Length (FT)                                                                                                                                                                                                            |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <br><b>PH</b> = Double Ended Cable with Male/Female Straight<br><b>PM</b> = Male Single Ended Straight<br><b>PN</b> = Male Single Ended 90°<br><b>PF</b> = Female Single Ended Straight<br><b>PG</b> = Female Single Ended 90°<br><b>PQ</b> = Double Ended Cable with Female 90°<br><b>PR</b> = Double Ended Cable with Male 90°<br><b>PS</b> = Double Ended Cable with (2) 90° Connectors<br><br><br><b>RF</b> = Female Receptacle*<br><br><br><b>RM</b> = Male Receptacle (Inlet)* | <b>20</b> = 20A up to 600V                                                                                                                                                   | <b>02</b><br><b>03</b><br><b>04</b><br><b>05</b> | <b>PA</b> = Green/Yellow<br>Black (all others)<br><br><b>PB</b> = Green/Yellow<br>White<br>Black (all others)<br><br><b>PE</b> = All Blue*** | <b>001</b> = 1'<br><b>005</b> = 5'<br><b>010</b> = 10'<br><b>015</b> = 15'<br><b>020</b> = 20'<br><b>025</b> = 25'<br><b>030</b> = 30'<br><b>035</b> = 35'<br><b>040</b> = 40'<br><b>045</b> = 45'<br><b>050</b> = 50' |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 20A up to 600V<br>Specialty construction<br>(Includes isolated ground<br>on 6 wire and #10 AWG super<br>neutral conductor on 5 and<br>6 wire devices, PB color<br>code only) | <b>03</b><br><b>04</b><br><b>05</b><br><b>06</b> |                                                                                                                                              |                                                                                                                                                                                                                        |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | <b>30</b> = 30A up to 600V                                                                                                                                                   | <b>04</b>                                        |                                                                                                                                              |                                                                                                                                                                                                                        |

Example: PH

23

06

PB

005

Note: \*1/2" NPT rear thread.

\*\*Other color codes available upon request.

\*\*\*Two wire only.

## Configurations (Male face view shown, female view is opposite)

|                                                |                                                                                     |                                                                                     |                                                                                      |                                                                                       |
|------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| <b>20 AMP</b>                                  |  |  |  |  |
| <b>20A SNIG</b><br>(with super neutral and IG) |  |  |  |  |
| <b>30 AMP</b>                                  |  |                                                                                     |                                                                                      |                                                                                       |

## Tees



TX2304002304T00

| Description                                 | Catalog Number         |
|---------------------------------------------|------------------------|
| LINKOSITY® M/F/F Tee, 20A, 2P               | <b>TX2002002002T00</b> |
| LINKOSITY® M/F/F Tee, 20A, 3P               | <b>TX2003002003T00</b> |
| LINKOSITY® M/F/F Tee, 20A, 4P               | <b>TX2004002004T00</b> |
| LINKOSITY® M/F/F Tee, 20A, 5P               | <b>TX2005002005T00</b> |
| LINKOSITY® M/F/F Tee, 20A SNIG, 4P          | <b>TX2304002304T00</b> |
| LINKOSITY® M/F/F Tee, 20A SNIG, 6P          | <b>TX2306002306T00</b> |
| LINKOSITY® M/F/F Tee, 20A SNIG, A Phase Tap | <b>TX2306002304A00</b> |
| LINKOSITY® M/F/F Tee, 20A SNIG, B Phase Tap | <b>TX2306002304B00</b> |
| LINKOSITY® M/F/F Tee, 20A SNIG, C Phase Tap | <b>TX2306002304C00</b> |
| LINKOSITY® M/F/F Tee, 30A, 4P               | <b>TX3004003004T00</b> |

## Closure Caps



CCMBC

| Description                        | For use with<br>Female Receptacle | Male Inlet   |
|------------------------------------|-----------------------------------|--------------|
| 20A and 30A Receptacle Closure Cap | <b>CCMBC</b>                      | <b>CCFBC</b> |