

PRISMATIC GLASS

Ceiling stem mounted • Dry location listed



Description:

Three-light linear LED chandelier with a bold and striking Prismatic Glass shade as the focal point of the fixture. This linear chandelier also features a sleek Brushed Nickel cap and stems, highlighting the industrial styling. The bottom of the fixture is enclosed with an etched glass diffuser.

Specifications:

- Brushed Nickel (-09) (plated)
- Steel construction
- Prismatic glass shades, Etched glass diffuser
- 120VA replaceable LED Module (part # 93054049)
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" hexagonal recessed outlet box
- Mounting strap for outlet box included
- 15 feet of wire supplied
- Two 6", one 12", one 15" lengths of stem included
- ENERGY STAR® qualified

Performance:

Number of Modules	3
Input Power	9w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW	623/69.2 (LM-79) per module
CCT	3000 K
CRI	90
Life (hours)	60,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30 °C
Max. Operating Temp	
Warranty	5 year warranty
Labels	cCSAus Dry location listed
	ENERGY STAR® qualified

P4715-0930K9

Images:



Dimensions:

Diameter: 9-1/8"
Length: 38"
Height: 12-5/8"
Overall Ht. W/Stem: 71-1/2"

PRISMATIC GLASS

Ceiling stem mounted • Dry location listed



P4715-0930K9

Dimming Notes:

P4715-0930K9 is designed to be compatible with many Electronic Low Voltage (ELV-Reverse Phase) controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron DVELV-300P

Lutron NTELV-300

Lutron VTELV-600

Lutron MAELV-600

Lutron SPELV-600

Leviton AWRMG-EAW

Leviton 6615-P

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.