

# PURE

Ceiling cord mounted • Damp location listed



## Description:

One-light LED pendant features designer oriented details. Antique Bronze finish with Natural Brass accents and an anodized gold interior. 3000K, 90+ CRI, 623 lumens.

## Specifications:

Antique Bronze (-20) (painted)  
Steel construction  
Aluminum Shade shade  
Dimmable (See Dimming Notes)  
Canopy covers a standard 4" hexagonal recessed outlet box  
Mounting strap for outlet box included  
10 feet of wire supplied  
ENERGY STAR® qualified

## Performance:

Number of Modules	1
Input Power	9w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW	623/69.2 (LM-79)
CCT	3000 K
CRI	90
Life (hours)	60,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30
Max. Operating Temp	30 °C
Warranty	5 year warranty
Labels	cCSAus Damp location listed ENERGY STAR® qualified

## P5175-2030K9

## Images:



## Dimensions:

Diameter: 6-1/2"  
Height: 8-7/8"  
Overall Ht. W/Cord: 130"

**P5175-2030K9****Dimming Notes:**

---

P5175-2030K9 is designed to be compatible with many Electronic Low Voltage (ELV-Reverse Phase) controls.

The following is a partial list of known compatible dimmer controls.

**Dimming Controls**

---

Lutron DVELV-300P

Lutron NTELV-300

Lutron VTELV-600

Lutron MAELV-600

Lutron SPELV-600

Leviton AWRMG-EAW

Leviton 6615-P

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.  
Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.