

Nano-Quick® 3 - 4 Pole Plugs and Receptacles

Choose the appropriate configuration from the Selector below.

Hubbell Logic Configurator

For example, catalog number **NCTA3105** is derived as follows:

DEVICE TYPE	RETENTION STYLE	BODY STYLE	POLES	CABLE TYPE	CABLE LENGTH (m)
NC = Plug, Female	T = Threaded, Locking S = Snap On	A = Right Angle S = Straight	3 4	1 = #24 AWG PVC Cable 2 = #24 AWG TPE Cable	** 02 05 **Replace with Length
↓	↓	↓	↓	↓	↓
NC	T	A	3	1	05

Note: Availability of specific items may vary. Consult factory for delivery. Use this chart to build plugs to meet any application need. Consult the factory for additional cable lengths or cable types.

3 - 4 Pole Female Plugs

Catalog numbers using #24 AWG PVC cable are listed below. For #24 AWG TPE cable, change the cable type per the Hubbell Logic chart above.

Poles	Female Face Shown	Cable Length	Threaded, Locking		Snap Together	
			Straight	Right Angle	Straight	Right Angle
3		6.56 ft (2m) 16.40 ft (5m) All other lengths ▲	NCTS3102 NCTS3105 NCTS31**	NCTA3102 NCTA3105 NCTA31**	NCSS3102 NCSS3105 NCSS31**	NCSA3102 NCSA3105 NCSA31**
4		6.56 ft (2m) 16.40 ft (5m) All other lengths ▲	NCTS4102 NCTS4105 NCTS41**	NCTA4102 NCTA4105 NCTA41**	NCSS4102 NCSS4105 NCSS41**	NCSA4102 NCSA4105 NCSA41**

Note: ▲ Replace ** with length required in feet. For snap on retention style, replace "T" with "S" per the ordering chart above.
Example: change NCTA3105 to NCSA3105.

Hubbell Logic Configurator

For example, Catalog Number **NBCS3D** is derived as follows:

DEVICE TYPE	RETENTION STYLE	BODY STYLE	POLES	CONDUCTOR TYPE
NB = Receptacle, Male	C = Combination	S = Straight	3 4	D = 0.25m #24 AWG discrete wire
↓	↓	↓	↓	↓
NB	C	S	3	D

3 - 4 Pole Male Receptacles

Poles	Male Face Shown	Male Receptacle Rear Thread Style
		M8 x 1
3		NBCS3D
4		NBCS4D

Note: Replace ** with length required in feet.