







Recessed 8-Gang Ballroom Series Floor Boxes

Dimensions Inches (mm)


| Style | CFB8FC Series | |
|--|--|---|
| | 8-Gang | 8-Gang |
|  |  CFB8FC1 |  CFB8FC2 |
| Application | Carpet | Tile, Finished Concrete |
| Min. Depth of Pour | 6.95" [177mm] | 7.15" [182mm] |
| Adjustability | Before Pour | Before Pour |
| Dimensions: | | |
| A | 6.95" (176.5) | 7.15" (181.6) |
| B | 15.00" (176.5) | 14.75" (374.7) |
| C | 13.00" (330.2) | 12.75" (323.9) |
| Trade Size Knockouts: | | |
| Sidewalls | (4) x 1.5", 1.25", 1" concentric | (4) x 1.5", 1.25", 1" concentric |
| Back | (4) x 1.5", 1.25", 1" concentric | (4) x 1.5", 1.25", 1" concentric |
| Bottom | (4) x 1.5", 1.25", 1" concentric | (4) x 1.5", 1.25", 1" concentric |
| Side View Depth behind mounting plate |  X = 2.27" (57.7) Y = 4.01" (101.9) Z = 3.13" (79.5) | X = 2.27" (57.7) Y = 4.01" (101.9) Z = 3.13" (79.5) |
| Accepts industry standard size wallplates (sold separately) 4.63" Maximum Cover Height | One, two, three and four gang plates. Customer configuration dependant. | One, two, three and four gang plates. Customer configuration dependant. |
| |  4-Gang 4-Gang |  4-Gang 4-Gang |

Accessories

On-grade Barrier

The on-grade barrier is intended for use on installations at grade level. This accessory is installed prior to the concrete pour and provides a barrier between the soil. The on-grade barrier comes with leveling feet and anchor points.

CFBOGPAN4



Pour Pan Dimensions:
15.75 in. sq.
4 in. depth

Covers

All ballroom floor box covers are machined from Aluminum and have no additional finish options

| | CFB8FC1 Covers | | CFB8FC2 Covers | |
|---|---|---|---|---|
| |  |  |  |  |
| Carpet Cover, with 2 egress doors (0.20" depth) | CFB8CVRALU1 | - | - | - |
| Flush cover, with 2 egress doors | - | - | CFB8CVRALU2 | - |
| Blank box cover | - | CFB8JBC1 | - | CFB8JBC2 |
| Cover Load Ratings*: | | | | |
| Recommended Loading | 20,000 lb | 20,000 lb | 20,000 lb | 20,000 lb |
| Maximum Load | 40,000 lb | 40,000 lb | 40,000 lb | 40,000 lb |

Note: *Load applied through 3" (76mm) mandrel in center of cover. Loads are static and don't apply to rolling loads.

Dimensions in Inches (mm)