




AFB series boxes are available from our factory as pre-wired assemblies with CONNEXION modular plug-n-play system

# SystemOne 4 inch Recessed Floor Box, for Raised Accessand Wood Floors

Description	Catalog Number
Floor Box with temporary installation Cover	AFBS1R4BASE
Floor Box (AFBS1R4BASE) with Brushed Aluminum Finish Cover (AFBS1R4CVRALU)	AFBS1R4ALU
Floor Box (AFBS1R4BASE) with Black Powder Coat Finish (AFBS1R4CVRBLK)	AFBS1R4BLK
Floor Box (AFBS1R4BASE) with Plated Brushed Brass Finish Cover (AFBS1R4CVRBRS)	AFBS1R4BRS
Floor Box (AFBS1R4BASE) with Plated Antique Bronze Finish Cover (AFBS1R4CVRBRZ)	AFBS1R4BRZ
Floor Box (AFBS1R4BASE) with Gray Powder Coat Finish Cover (AFBS1R4CVRGRY)	AFBS1R4GRY
Floor Box (AFBS1R4BASE) with Plated Satin Nickel Finish Cover (AFBS1R4CVRNKL)	AFBS1R4NKL



Replacement Parts

Description	Catalog Number
Low Voltage Divider	AFBS1R4DIV
Replacement Bottom Knockouts	AFBS1R4BOTTOM

#### Installation


Hole Diameter	4 inch
Bottom Knock out	1 inch, ¾ inch, ½ inch concentric
Side knock out	(4) ½ inch

#### Covers

- Flange diameter is 5.5 inches
- Flange thickness is 1/8 inches thick and complies with **ADA** requirements

Note: \*Load applied through a 3 in. (76mm) mandrel in center of the cover.

• Cover load rating is 1,000 lbs, for a static load applied through a 3 inch dia. mandrel with 2x safety factor\*





AFBS1R4BLK




AFBS1R4DIV



AFBS1R4BOTTOM

### **Architectural Covers**

Description / Catalog Number	Cover	Description / Catalog Number	Cover
Brushed Aluminum Finish, Single fold under cable egress door.		Plated Antique Bronze Finish, Single fold under cable egress door.	T
AFBS1R4CVRALU		AFBS1R4CVRBRZ	







Plated Satin Nickel Finish, Single fold under cable earess door.

AFBS1R4CVRNKL



### **Powder Coat Covers**

Description / Catalog Number	
Black Powder Coat Finish,	
Single fold under cable	
egress door.	



Gray Powder Coat Finish, Single fold under cable egress door.

AFBS1R4CVRGRY



Cover

## **Device Mounting Plates**

Device Mounting Plates					
Description / Catalog Number	Sub-plate	Description / Catalog Number	Sub-plate	Description / Catalog Number	Sub-plate
2X2 Sub-plate with (1) Style Line® decorator device opening and (2) keystone jack openings S1R4SP2X2STYLE	0	(1) Style Line® decorator device opening for power or datacom applications  S1R4SPSTYLE	0	2X2 Sub-plate with (1) decorator device opening and (2) Ortronics® TracJack® openings \$1R4\$P2X2\$TYLETJ	0
2X2 Sub-plate with (1) duplex device opening and (2) keystone jack openings S1R4SP2X2DUPLEX	8	(1) Duplex device opening for power or datacom applications  S1R4SPDUPLEX	8	2X2 Sub-plate with (1) duplex device opening and (2) Ortronics® TracJack® openings S1R4SP2X2DUPLEXTJ	0
(4) Single 20A receptacles. Can be wired as single or two circuit with isolated ground capability, 12 inch wire leads Includes 🖰 stickers.		(1) 1.60 inch opening for 20 or 30A Twist-Lock® receptacle	0	(1) 1.40 inch opening for simplex receptacle	0
S1R4SPQUAD		S1R4SPTWIST		S1R4SPSIMPLEX	

TracJack®, Series II® and Ortronics® are registered trademarks of Ortronics/Legrand.

Dimensions in Inches (mm)