

MIDGET TWIST-LOCK® PLUG OR CONNECTOR BODY

Installation Instructions

GENERAL INFORMATION

CAUTION: RISK OF ELECTRIC SHOCK.

- DISCONNECT ELECTRICAL POWER BEFORE INSTALLATION OR MAINTENANCE.
- NEVER WIRE ENERGIZED ELECTRICAL COMPONENTS.

CAUTION: USE COPPER CONDUCTORS ONLY.

NOTICE:

- FOR INSTALLATION BY A QUALIFIED PERSON IN ACCORDANCE WITH NATIONAL AND LOCAL ELECTRICAL CODES.
- CHECK THAT THE DEVICE TYPE AND RATING IS SUITABLE FOR THE APPLICATION PRIOR TO INSTALLATION.

WIRE INFORMATION

- 1.) CORD GRIP RANGE.
ACCEPTS CONDUCTOR / CORD SIZES 18/3 TYPE SJ TO 14/3 TYPE SJ (.281 TO .421 DIA.)
- 2.) SELECT THE PROPER WIRE SIZE AND TYPE FOR LOAD AND APPLICATION. REFER TO N.E.C. TABLES, ARTICLE 400.
- 3.) SEE FIGURE 1 BELOW FOR STRIP LENGTH.
- 4.) DO NOT TIN CONDUCTORS.




FIGURE 1



RECOMMENDED
TERMINAL SCREW
WIRE WRAP
(WIRE ENTERS FROM INSIDE)

NOTE: THE LENGTH OF THESE DEVICES HAS BEEN ALTERED TO COMPLY WITH THE LATEST REQUIREMENTS OF UNDERWRITERS LABORATORIES, INC.

