4 IN. SQUARE WELDED BOXES - 2-1/8 IN. DEEP WITH ARMORED CABLE / METAL CLAD / FLEX CLAMPS

4 in. Square Welded Boxes - 2-1/8 in. Deep with Armored Cable / Metal Clad / Flex Clamps
4 Square Box 2-1/8 in. Deep w/Top STAB-IT M-Brkt CM **A18**



Catalog #: 244MSCM

APPLICATIONS

RACO® STAB-IT boxes are great for any job where flexible armored cable is being used
RACO® Boxes are installed in walls or ceilings for lighting fixtures, switches or receptacles

PRODUCT FEATURES

Designed for quick installation of flex, MC, MCI, MCI-A, AC, and HCF Cable
TKO® Knockouts offer greater flexibility with RACO patented combination 1/2 in. and 3/4 in. knockout
UBS Support - Welded to box, preset bend points to work with wall thickness 2-1/2 in. to 6 in.

UL LISTED

File E195978

COMPLIANCES

All RACO® single gang, two gang, 4 in. square, and single gang gangable UL listed steel boxes are acceptable for use in 2-hour fire rated walls. For additional information, consult UL "Fire Resistance Directory" or the UL website at www.ul.com
600V Per UL 514-A, suitable for use without a bonding jumper in circuits up to 600 volts
MSDS
www.hubbell-rtb.com/certifications/Hubbell-RACO_MSDS_for_Steel_Boxes_and_Covers.pdf

FIRE RESISTANCE

Acceptable for use in 2-hour rated walls

GENERAL PRODUCT INFORMATION

Wiring System:	Armored Cable/Metal Clad/MCI-A/Flex

CONFIGURATION

Cable Priouts:	4
Bracket Type:	M Bracket
Drawn or Welded:	Welded
Raised Ground:	Yes
Side Knockout(s):	(4) 1/2 in., (2) 1/2 in. - 3/4 in. TKO
Bottom Knockouts(s):	(1) 1/2 in., (1) 1/2 in. - 3/4 in. TKO

PRODUCT MEASUREMENTS

Depth:	2-1/8 in.
Cubic Inches (cm3):	30.3 (496.5)
Wt. Ea. (Lbs.):	1.339
Product Length (in.):	2.64
Product Width (in.):	5.86
Product Height (in.):	4.17

PACKAGING

Minimum Pack Qty.:	25
Std. Pkg.:	25
Product UPC-A Labeled:	No
Weight (Lbs. Per/C):	133.904
Ship Carton Length (in.):	20.875
Ship Carton Width (in.):	8.00
Ship Carton Height (in.):	8.500
Ctn Weight (Lbs.):	33.476
Pallet Qty:	1375
UPC Number:	050169972441
I2of5:	50050169972446