



30 Amp, 125/250 and 3Ø 250 Volts AC 3 Pole, 3 Wire, Non-Grounding and 3 Pole, 4 Wire, Grounding



Catalog Number

HBL2663



IP20 SUITABILITY

HBL2713

HBL27CM13

HBL2713BK



HBL2723

Connector Bodies

Watertight Safety-Shroud®

IP66 SUITABILITY UL Type 4x, 12



Description	Cord Dia.	Catalog Number		
Black Valox® housing, white Valox® clamps.	.350"-1.150" (9-29)	-	HBL2713SW	HBL2723SW
Reverse service, black Valox® housing, white Valox® clamps (use with HBL2715SWR), (Not shown).	.350"-1.150" (9-29)	-	HBL2713SR	-

Cord Dia.

(7.6-24.1)

.350"-1.150"

.350"-1.150"

(9-29).300"-.950"

(9-29)

(9-29)

.350"-1.150"

HBL27CM23



Note: See page B-52 for accessories.

Corrosion resistant, yellow nylon.

Receptacles

Insulgrip®

All black nylon.

Black and white nylon.

Black and white nylon, (Not shown).

Description

Watertight Safety-Shroud®	IP66	SUITABILITY	UL Type 4x, 12
Description	Catalog Number		
Gray Valox® housing and flange, back wired.	-	HBL2710S\	W HBL2720SW
Note: See page B-54 for accessories.			

Safety-Shroud® Twist-Lock®

Salety-Silioud Twist-Lock	IPZU SUITABILITY		
Description	Catalog Number		
Gray Valox® angle housing, one gang, back wired.	-	HBL2710AR	HBL2720AR
Gray Valox® surface mounting, one gang, back wired.	-	HBL2710SR	HBL2720SR
Gray Valox® semi-flush, two gang, back wired.	-	HBL2710SR2	HBL2720SR2



Single Flush Receptacles		IP20 SUITABILI	ГУ
Description	Catalog Number		
Black nylon face, back and side wired.	_	HBL2710	HBL2720
Black nylon face, back and side wired, (Not shown).	HBL2660	-	-
Isolated ground, orange nylon face, back and side wired.	-	IG2710	IG2720
Ring terminal connection.	_	HBL2710RT	HBL2720RT

Note: See page B-52 for accessories.

4.58" (116.3) HBL2710AR


Insulgrip [®] Flanged Receptacle

Description	Catalog Number			
Nylon casing, back wired.	-	HBL2716	HBL2726	

Note: See page B-52 for accessories.









Valox® is a trademark of SABIC Innovative Plastics, acquired from General Electric Company.

Dimensions in Inches (mm)