

# 120V AC LED PUCK

## LED PUCK

**P7510-30** White  
120V LED puck.  
3-1/4" dia., 15/16" ht.  
4w LED array.  
Damp location listed.



P7510-30



*Quick connect locations on two sides and the top.*

PROGRESS **LED**

HIDE a **LITE 3**

## Electrical

120V AC linkable LED puck.

## Lamping

Long life LED's 50,000 hours, 70% lumen maintenance. 3000K color temperature, 85+ CRI.

## Construction

Die cast enclosure. V5 rated cover and frosted lens.

## Linkable

This system can be powered from a single location using the P8740 direct-wire junction box using HAL3 linking cables (P8733, P8737, P8738, P8739). The fixtures can be linked together to form a continuous row of illumination.

## Dimming

Smooth and continuous dimming using many incandescent and ELV dimmers (Note: Reference dimmer manufacturer's minimum load requirements.)

## LINKING CABLES FOR HAL 3



P8733-30

**P8733-20** Antique Bronze  
**P8733-30** White  
12" Undercabinet fixture linking cable.  
12" L., 3/4" W., 3/8" ht.



P8735-20

**P8735-20** Antique Bronze  
**P8735-30** White  
6" Undercabinet fixture linking cable.  
6" L., 3/4" W., 3/8" ht.



P8737-30

**P8737-20** Antique Bronze  
**P8737-30** White  
18" Undercabinet fixture linking cable.  
18" L., 3/4" W., 3/8" ht.



P8738-30

**P8738-20** Antique Bronze  
**P8738-30** White  
24" Undercabinet fixture linking cable.  
24" L., 3/4" W., 3/8" ht.

## JUNCTION BOX FOR HAL 3

### HAL3 JUNCTION BOX.

**P8740-20** Antique Bronze  
**P8740-30** White  
3-1/2" L., 3-1/4" W., 1" ht.

### COUPLING CABLE

**P8743-20** Antique Bronze  
**P8743-30** White  
Connects two linking cables together.  
6" L., 7/5" W., .5" ht.




P8740-30



P8743-20



*Side view showing cable connector*



*Shown P8740-30 with P8737-30*