

6" LED FIRE RATED

HOUSINGS & TRIMS

For complete fixture, order housing with trim.



P821-FBLED

- IC rated
- Fits into 2" x 10" construction
- CUL and UL listed for wet location when used with P8071 (sold separately)
- UL classified to maintain fire ratings of 2 hour or less (see spec sheet for ceiling/floor designs)



P821-FBLED

Ceiling opening: 6-7/8"
Plaster frame: 13-3/8" x 9-9/16"
Recessed depth: 9-3/16"
Pryouts: 1/2" & 3/4"

6" LED 800 LUMENS ELV DIMMER

P8071-20/30K9-AC1-L08 Antique Bronze
P8071-28/30K9-AC1-L08 White
P8071-31/30K9-AC1-L08 Black
P8071-82/30K9-AC1-L08 Metallic Gray



P8071-20/30K9-AC1-L08



P8071-28/30K9-AC1-L08



P8071-31/30K9-AC1-L08



P8071-82/30K9-AC1-L08

6" LED 1000 LUMENS TRIAC DIMMER

P8071-28/30K9-L10-STR2 White
P8071-28/35K9-L10-STR2 White



P8071-28/30K9-L10-STR2



P8071-28/35K9-L10-STR2

6" LED 700 LUMENS ELV DIMMER

P8071-2030K9-AC1-L07 Antique Bronze
P8071-2830K9-AC1-L07 White
P8071-3130K9-AC1-L07 Black
P8071-8230K9-AC1-L07 Metallic Gray



P8071-2030K9-AC1-L07



P8071-2830K9-AC1-L07



P8071-3130K9-AC1-L07



P8071-8230K9-AC1-L07

6" LED 700 LUMENS TRIAC DIMMER

P8071-09-30K Brushed Nickel
P8071-20-30K Antique Bronze
P8071-28-30K White
P8071-31-30K Black



P8071-09-30K



P8071-20-30K



P8071-28-30K



P8071-31-30K