

5" INCANDESCENT

HOUSINGS & TRIMS

For complete fixture, order housing with trim.

Standard IC and Non-IC Universal Housings

New Construction Air-Tight IC



P85-AT

Ceiling opening: 5-1/4"
Plaster frame: 8-3/8" x 13"
Recessed depth: 7-5/8"
Pryouts: 1/2" & 3/4"

P85-AT

- Rated for direct contact with ceiling insulation
- Trims are Easy-in and push-lock into place
- Notched mounting frame for easy alignment
- Slotted, interlocking bar hangers provide solid mounting on 24" centers.
- P85-AT meets Washington State Energy Code requirements
- Can be installed in ceilings from 1/2" to 2" thickness

New Construction Non-IC



P85-TG

Ceiling opening: 5-1/4"
Plaster frame: 7-7/8" x 10-3/4"
Recessed depth: 7-1/2"
Pryouts: 1/2" & 3/4"

P85-TG

- Nail grip bar hangers accommodate 24" on center ceiling joists or T-bars, and have locking feature to secure housing in place
- Integral T-bar clamps on bar hangers
- Complete with grounding pigtail
- UL and CUL Listed for damp locations and through wiring
- Integral Romex clamps
- Rated for 8 #12 90° conductors (4 in/4 out)
- Can be installed in ceilings from 1/2" to 2" thickness

Remodel Non-IC



P185-TG

Ceiling opening: 5-1/8"
Recessed depth: 7-1/2"
Pryouts: 1/2"

P185-TG

- Locking clips (furnished) permit quick mounting in ceiling
- Can be installed in ceilings 1/2" to 1"
- Rated for 4 #12 90° conductors (2 in/2 out)
- Rated 60° supply wires in end-of-run applications.
- Trims are easy in and push into place

IC/Non-IC Trims

For insulated and non-insulated ceilings. 6-1/8" outside diameter, except where indicated.



OPEN

P8168-28 White
65w BR30, 50w PAR 30
Long Neck
85w BR30, 75w PAR 30
Long Neck, 60w A19



EYEBALL

P8176-28 White
6-3/8"
75w PAR30 Short Neck



DEEP CONE

P8172-09 Brushed Nickel
65w BR30, 50w PAR30
Short Neck
85w BR30, 75w PAR30
Short Neck



DEEP CONE

P8172-21A Clear Alzak®
P8172-22A Gold Alzak®
White flange
65w BR30, 50w PAR30
Short Neck
85w BR30, 75w PAR30
Short Neck



STEP BAFFLE

P8175-31 Black
P8175-28 White
65w BR 30, 50w PAR 30
Long Neck
65w BR 30, 50w PAR-30
Long Neck, 40w A19



STEP BAFFLE

P8175-20 Antique Bronze
65w BR 30, 50w PAR 30
Long Neck
65w BR 30, 50w PAR-30
Long Neck, 40w A19



OPEN SHOWER TRIM

P8367WL-28 White
Wet location listed
Metal flange
50w PAR 30 Short Neck*



SHOWER LIGHT

P8109-28 White
Wet location listed
Metal flange
40w A19, 50w PAR30
60w A19, 75w PAR30

Lamp wattages shown are maximum.
Patent Pending

* WL trims require use with outdoor rated PAR lamps