
AFB series boxes are available from our factory as pre-wired assemblies with



SystemOne Recessed 10-Gang Rectangular Floor Boxes, Covers and Plates For Use In Raised Access or Wood Floors

Dimensions Inches (mm)





Box Type	
Standard Chicago	AFB10G55 AFB10G55CHI
Min. Depth from Top of Floor Tile	5.50" (139.7)
Cubic Inch (cm3) Capacity per Gang	25 cu. in. (400 cm3)
Dimensions – A	5.74" (145.9)
Dimensions – B	10.96" (278.4)
Dimensions – C	12.37" (314.1)
KO Trade Size: Front & Back Sides Bottom	(1) ½", ¾", (1) ¾", 1", 1¼", 1½", (1) 1", 1¼", 1½", 2" (2) ¾", 1", 1¼", 1½" (2) ½", ¾", (4) ½", ¾", 1", 1¼"
Cover Family	Rectangular
Temporary Cover Included	✓

CONNEXION modular plug-n-play system





Rectangular Covers

0.00

(for use with raised access tiles and wood floors)


- Die cast construction available in five finishes
- UL 514A listed
- Maximum static load of 1500 lbs with 2x safety factor*

Finish	Surface Style Cover	Surface Style Cover with Insert
Aluminum Powder Coat Black Powder Coat Brass Powder Coat Bronze Powder Coat	10GAFBCVRALU 10GAFBCVRBK 10GAFBCVRBRS 10GAFBCVRBRZ	10GAFBCVRALUC 10GAFBCVRBKC 10GAFBCVRBRSC 10GAFBCVRBRSC
Satin Nickel Powder Coat	10GAFBCVRNK	10GAFBCVRNKC

Note: *Load applied through a 3 in. (76mm) mandrel in center of the cover.

AFB10 Series - Plates

			N. Carlotte	THE RESERVE TO SERVE	100
Cat. No.	FB10MPREC	FB10MPDUP	FB10MPBNK	FB10MPKEY	FB10MPTRAC
Style	Opening	Opening	Blank	Including Hubbell ISF6GY	(6) Ortronics TrackJack®
Plate	(1) Decorator	(1) Duplex		Decorator Opening Plate	(2) Openings to Accommodate













Cat. No.	FB10TLA	FB10TLX	FB10TLB	FB10TLY	FB10MP3GAPP	
Plate Style	1.60 in. Dia. (Uses 2-Gangs)	1.40 in. Dia. (Uses 2-Gangs)	1.60 in. Dia. (Uses 3-Gangs)	1.40 in. Dia. (Uses 3-Gangs)	Receptacle (Uses 3-Gangs)	
	(1) Twist-Lock® Opening	(1) Simplex Opening	(2) Twist-Lock® Opening	(2) Simplex Opening	(1) Opening for Appliance	









(2) 2-Gang. Meets NEMA Spacing.



(4) Single Service Openings

Plate Style	(3) Twist-Lock Opening 1.60 in. Dia. (Uses 5-Gangs)	(3) Simplex Opening 1.40 in. Dia. (Uses 5-Gangs)	Ideal for Crestron DM -TX Product and Power (Uses 5-Gangs)	Utilizing NEMA Wallplate (Uses 5-Gangs)
Cat. No.	FB10TLC	FB10TLZ	CFB10NEMA	FB10MPNEMA4G
			and the same of	1111







Extron® is a registered trademark of Extron Electronics. Crestron® is a registered trademark of Crestron Electronics, Inc. FSR® is a registered trademark of FSR Inc. TracJack®, Series II® and Ortronics® are registered trademarks of Ortronics/Legrand.

Dimensions in Inches (mm)