




## Duct Sealing Compound

## Duct Sealing Compound

**B89.1**

Catalog #: DS-1LB

**APPLICATIONS**

RACO Duct Sealing Compound is an asbestos free, non-toxic general sealing compound for use in indoor or outdoor applications. Common uses include sealing around electrical boxes, flashings, and mast service entries. It is permanently soft and will adhere to most clean dry surfaces.

**PRODUCT FEATURES**

Non-corrosive: safe for metals and plastics  
Non-Irritant to skin  
Paintable  
Recommended temperature usage range: 25° to +120°F  
Temperature tolerance range: -30° to +175°F  
Will not slump at +275°F  
Gray Color

**UL LISTED**

UL Classified R38734

**CULUS**

N/A

**COMPLIANCES**

MSDS  
[www.hubbell-rtb.com/certifications/MSDS\\_2016\\_1.pdf](http://www.hubbell-rtb.com/certifications/MSDS_2016_1.pdf)

**GENERAL PRODUCT INFORMATION**

Color: Gray

**PACKAGING**

Package Type:	Carton
Ship Carton Qty.:	30
Product UPC-A Labeled:	No
Weight (Lbs. Per/C):	106.50
Ship Carton Length (in.):	14.63
Ship Carton Width (in.):	11.50
Ship Carton Height (in.):	4.63
Ctn Weight (Lbs.):	31.94
UPC Number:	050169900017
I2of5:	50050169900012