
4 IN. SQUARE WELDED BOXES - 2-1/8 IN. DEEP WITH ARMORED CABLE / METAL CLAD / FLEX CLAMPS

4 in. Square Welded Boxes - 2-1/8 in. Deep with Armored Cable / Metal Clad / Flex Clamps 4 Square Box 2-1/8 in. Deep w/STAB-ITs on top CM 600V, 8" #12 Solid Copper Pigtail

A18





Catalog #: 244SCM

APPLICATIONS

RACO® STAB-IT boxes are great for any job where flexible armored cable is being used RACO® Boxes are installed in walls or ceilings for lighting fixtures, switches or receptacles

PRODUCT FEATURES

Designed for quick installation of flex, MC, MCI, MCI-A, AC, and HCF Cable TKO® Knockouts offer greater flexibility with RACO patented combination 1/2 in. and 3/4 in. knockout

UL LISTED

File E195978

COMPLIANCES

All RACO® single gang, two gang, 4 in. square, and single gang UL listed steel boxes are acceptable for use in 2-hour fire rated walls. For additional information, consult UL "Fire Resistance Directory" or the UL website at www.ul.com

600V Per UL 514-A, suitable for use without a bonding jumper in circuits up to 600 volts

 $\underline{www.hubbell\text{-}rtb.com/certifications/Hubbell\text{-}RACO_MSDS_for_Steel_Boxes_and_Covers.pdf}$

FIRE RESISTANCE

Acceptable for use in 2-hour rated walls

GENERAL PRODUCT INFORMATION

Wiring System: Armored Cable/Metal Clad/MCI-A/Flex

CONFIGURATION

Cable Priouts No Bracket Bracket Type: Welded Drawn or Welded: Raised Ground:

(4) 1/2 in., (2) 1/2 in. - 3/4 in. TKO (1) 1/2 in., (1) 1/2 in. - 3/4 in. TKO Side Knockout(s):

Bottom Knockouts(s):

PRODUCT MEASUREMENTS

2-1/8 in. 30.3 (496.5) Depth: Cubic Inches (cm3): 1.231 Wt. Ea. (Lbs.): Product Length (in.): 2.430 Product Width (in.): 4.00 4.15 Product Height (in.):

PACKAGING

25 Minimum Pack Qty.: Std. Pkg.: Product UPC-A Labeled: 25 No 123.136 Weight (Lbs. Per/C): Ship Carton Length (in.): 18.750 7.375 Ship Carton Width (in.): Ship Carton Height (in.): 8.500 30.784 Ctn Weight (Lbs.): 1750 Pallet Qty:

050169962442 UPC Number: 50050169962447 12of5:

Page 4 / 4