

WCY61PB

by Burndy
Catalog ID: WCY61PB

Prop 65 Notice

Wejtap Tap Connector, 397.5-477 Std 477-636 18/1 Cmpct,450-556.5 Std, 477-636 Cmpct Al&Cu (Run), 477 Std. 556.5-636 18/1 Cmpct, 477-556.5 Std, 550-636 cmpct Al&Cu (Tap).

Features: With Yellow Power Booster, ANSI Class AA, Booster Color: Yellow, Conductor Size (tap - Mm): 17 - 24 SQ-MM, Installation Tool: WTRB, WTY Tool, Color Code: Yellow, Booster: WPBY Box 25, Conductor Type: Run: ACSR, AAC, Tap: ACSR, AAC, Copper, Cable Diameter Range (run): 0.683 - 0.94 IN, Conductor Size (run - Mm): 17 - 24 SQ-MM, Cable Diameter Range (tap): 0.666 - 0.94 IN

Product Details

General

Application	For use in tap applications using large run and tap conductor sizes
Color	Yellow
Connector Type	Tap
Material	Copper
Sub Brand	WEJTAP
Trade Name	WEJTAP™
Type	Wejtap Connector with Booster
UPC	781810870556
UPC 12 Digit	7818108705566

Dimensions

Dimension - F Width Center to Center inch	3 in
Dimension - G inch	1.53 in

Conductor Related

Conductor - ACSR Str Run	336.4 (18/1) Merlin;336.4 (26/7) Linnet;336.4 (30/7) Oriole;397.5 (18/1) Chickadee;397.5 (24/7) Brant;397.5 (26/7) Ibis;397.5 (30/7) Larkspur;477.0 (18/1) Pelican;477.0 (24/7) Flicker;477.0 (26/7) Hawk;477.0 (30/7) Hen;556.5 (24/7) Parakeet;556.5 (26/7) Dove;556.5 (30/7) Eagle
Conductor - ACSR Str Run Range	336.4 (18/1) Merlin-556.5 (30/7) Eagle
Conductor - ACSR Str Tap	266.8 (26/7) Partridge;300.0 (26/7) Ostrich;336.4 (18/1) Merlin;336.4 (26/7) Linnet;336.4 (30/7) Oriole;397.5 (18/1) Chickadee;397.5 (24/7) Brant;397.5 (26/7) Ibis;397.5 (30/7) Larkspur;477.0 (18/1) Pelican;477.0 (24/7) Flicker;477.0 (26/7) Hawk;477.0 (30/7) Hen;556.5 (24/7) Parakeet;556.5 (26/7) Dove;556.5 (30/7) Eagle
Conductor - ACSR Str Tap Range	266.8 (26/7) Partridge-556.5 (30/7) Eagle
Conductor - AL Str Run	350;397.5;400;450;477;500;550;556.5;600;636;650;700
Conductor - AL Str Run Range	350-700
Conductor - AL Str Tap	336.4;350;397.5;400;450;477;500;550;556.5;600;636;650;700
Conductor - AL Str Tap Range	336.4-700

Conductor Type	• ACSR C Str-Run • AL C Str-Run • ACSR C Str-Tap • AL C Str-Tap
----------------	---

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	NC
UL Listed	No

Logistics

Minimum Pack Quantity	5
-----------------------	---

For further technical assistance, please contact us

BURNDY Headquarters
47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:
8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)