

6" HIGH WATTAGE

HIGH WATTAGE IC HOUSINGS & TRIMS

For complete fixture, order housing with trim.

New Construction or Top Accessible
Ceilings Air-Tight IC



P821-AT
Ceiling opening: 6-7/8" dia.
Plaster frame: 8-3/8" x 13"
Recessed depth: 7-5/8"
Pryouts: 1/2" & 3/4"

P821-AT

- Allows for high wattage in insulated ceilings up to 150w
- Meets Washington State Energy Code requirements
- Can be installed in ceilings from 1/2" to 2-1/2" thick
- UL and CUL listed for damp locations and through wiring
- Socket mounts to trim for consistent lamp position
- Spans 24" T-bar spacing
- Integral Romex clamp
- Integral nailer and T-bar mounting clamp
- Rated for 8 #12 90° conductors (4 in/4 out)
- US Patent #5758959, 5857766, 6004001

IC TRIMS



STEP BAFFLE
P8075-28 White
P8075-31 Black
85w BR30, 75w PAR30
Long Neck, 75w A19



STEP BAFFLE
P8066-20 Antique Bronze
120w BR40, 150w PAR 38,
100w A19



STEP BAFFLE
P8066-09 Brushed Nickel*
P8066-31 Black
120w BR40, 150w
PAR 38, 100w A19
*Unpainted flange



STEP BAFFLE
P8066-28 White
120w BR40, 150w PAR
38, 100w A19



STEP BAFFLE
P8082-28 White
P8082-31 Black
8-3/4"
150w BR40,
150w PAR 38



CONES
P8053-31 Black Alzak®
Black Flange
150w PAR 38, 120w BR
40, 100w A19



CONES
P8068-22A Gold Alzak®
P8068-21A Clear Alzak®
P8068-28 White
White Flange
120w BR 40, 150w PAR
38, 100w A19



WALL WASHER
P8052-28 White Baffle
40w A19



EYEBALL
Rotates 358°, tilts 30° max.
P8076-09 Brushed Nickel
P8076-20 Antique Bronze
P8076-28 White
85w BR30, 75w PAR 30



BAFFLED EYEBALL
Rotates 358°, tilts 30° max.
P8079-28 White Baffle
P8079-31 Black Baffle and
Black Eyeball
85w BR30, 75w PAR 30



BAFFLED MINI EYEBALL
Rotates 358°, tilts 30° max.
P8077-28 White Baffle
75w R20, PAR 16, PAR 20



REGRESSED MINI EYEBALL
Rotates 358°, tilts 30° max.
P8078-28 White
75w R 20, PAR 16, PAR 20



OPEN SPLAY
P8072-28 White
85w BR30, 75w PAR 30
Long Neck, 75w A19



OPEN
P8074-28 White
8-3/4"
120w BR40, 150w PAR 38



FRESNEL
Wet location listed
P8062-28 White
Metal flange
40w A19



ALBALITE
Wet location listed
P8060-28 White
Metal Flange
40w A19



FRESNEL
Wet location listed
P8011-60 White
Non-metallic flange
50w PAR30 Short Neck



DROP OPAL SHOWER
Wet location listed
P8007-60 White
Metal flange
75w A19, 75w PAR 30



DROP OPAL SHOWER
Wet location listed
P8009-60 White glass
Non-metallic flange
60w A19, 75w PAR 30



OPEN SHOWER TRIMS
Wet location listed
P8072WL-28 White
Metal flange
50w PAR 30 Long Neck
P8074WL-28 White
8-3/4"
75w PAR 38*



DOME SHOWER
Wet location listed
P8025-60 White
Polycarbonate
8-3/4" outside diameter
60w A19

Lamp wattages shown are
maximum.