

Metal PlugTrak® Series

Available in Standard, Isolated Ground (IG), Tamper-Resistant (TR) and USB (U) versions.



USB



Tamper-Resistant

	Amp Circuits	Single Recept.	USB Ports	Receptacle Spacing (in.)	Ivory		Gray	
3 Foot	15 Single	6	—	6	HBL20GB306IV		HBL20GB306GY	
	15 IG/Single	6	—	6	HBL20IG306IV		HBL20IG306GY	
	15 TR/Single	6	—	6	HBL20GB306IVTR		HBL20GB306GYTR	TR
	15 USB/Single	2	2	12	HBL20GB312UIV		—	TR USB
	20 Single	6	—	6	HBL24GB306IV		HBL24GB306GY	
	20 TR/Single	6	—	6	HBL24GB306IVTR		HBL24GB306GYTR	TR
5 Foot	15 Single	10	—	6	HBL20GB506IV		HBL20GB506GY	
	15 Single	5	—	12	HBL20GB512IV		HBL20GB512GY	
	15 Two	5	—	12	HBL20GBA512IV		HBL20GBA512GY	
	15 IG/Single	5	—	12	HBL20IG512IV		HBL20IG512GY	
	15 TR/Single	5	—	12	HBL20GB512IVTR		HBL20GB512GYTR	TR
	20 Single	10	—	6	HBL24GB506IV		HBL24GB506GY	
	20 Single	5	—	12	HBL24GB512IV		HBL24GB512GY	
	20 Two	5	—	12	HBL24GBA512IV		HBL24GBA512GY	
6 Foot	20 TR/Single	5	—	12	HBL24GB512IVTR		HBL24GB512GYTR	TR
	15 Single	12	—	6	HBL20GB606IV		HBL20GB606GY	
	15 Single	8	—	9	HBL20GB609IV		HBL20GB609GY	
	15 Single	6	—	12	HBL20GB612IV		HBL20GB612GY	
	15 Single	4	—	18	HBL20GB618IV		HBL20GB618GY	
	15 Two	8	—	9	HBL20GBA609IV		HBL20GBA609GY	
	15 Two	6	—	12	HBL20GBA612IV		HBL20GBA612GY	
	15 Two	4	—	18	HBL20GBA618IV		HBL20GBA618GY	
	15 IG/Single	12	—	6	HBL20IG606IV		HBL20IG606GY	
	15 USB/Single	4	4	12	HBL20GB612UIV		—	TR USB
	20 Single	12	—	6	HBL24GB606IV		HBL24GB606GY	
	20 Single	6	—	12	HBL24GB612IV		HBL24GB612GY	
	20 Single	4	—	18	HBL24GB618IV		HBL24GB618GY	
	20 Two	6	—	12	HBL24GBA612IV		HBL24GBA612GY	
	20 Two	4	—	18	HBL24GBA618IV		HBL24GBA618GY	



Portable	Amp Circuits	Length (in.)	Cord Length (ft.)	Single Recept.	USB Ports	Ivory		Gray	
	15 Single	40	6	6	—	HBL20C215IV		HBL20C215GY	
	15 USB/Single	40	6	4	2	HBL20C215UIV		—	TR USB
	15 Single	64	6	10	—	HBL20C315IV		HBL20C315GY	

Note: IG = Isolated Ground, TR = Tamper-Resistant and U = USB.

Hubbell Metal PlugTrak is supplied with two HBL2010BIV/GY blank end fittings and one HBL2001C coupling. Catalog number suffix "IV" for ivory finish and "GY" for gray finish. Outlets match raceway color. "IG" Isolated ground receptacles have orange triangles. Portable PlugTrak includes 15A circuit breaker.

Dimensions in Inches (mm)

	Description	Color	Catalog Number
Boxes	1-Gang Device Box	Ivory Gray	HBL2048IV HBL2048GY
	2-Gang Device Box	Ivory Gray	HBL20482IV HBL20482GY
Elbows and Tees	External Elbow	Ivory Gray	HBL2018CIV HBL2018CGY
	Flat Elbow	Ivory Gray	HBL2011IV HBL2011GY
	Tee	Ivory Gray	HBL2015IV HBL2015GY
	Entrance End Fitting	Ivory Gray	HBL2010A2IV HBL2010A2GY
End Fittings	Large Entrance End Fitting	Ivory Gray	HBL2010A3IV HBL2010A3GY
	Blank End Fitting	Ivory Gray	HBL2010BIV HBL2010BGY
	Cover Clip	Ivory Gray	HBL2006IV HBL2006GY
Fittings	Supporting Clip	Steel**	HBL2003SC*
	Coupling	Steel**	HBL2001C
	Internal Corner Coupling	Steel**	HBL2017TC

Note: *Support clip HBL2003SC for supporting Portable Metal PlugTrak only.

**Galvanized Steel.

See pages T-10 and T-11 for additional information.